© 2019 Moody•Nolan, Inc.

2 PLAN
SCALE 3/32" = 1'-0"
NEW FLOOR
0 4 8 16

1 PLAN
SCALE 3/32" = 1'-0"
NEW FLOOR
0 4 8 16

3 PLAN
SCALE 1/8" = 1'-0"
ENLARGED
0 3 6 12

4 PLAN
SCALE 1/8" = 1'-0"
ENLARGED
0 3 6 12

General Notes

1. REFER TO THE "DESIGN GUIDELINES OF PREP AREAS USING INSULATED CEILING AND WALL PANELS" IN THE PROJECT MANUAL FOR THE CONTRACTORS RESPONSIBILITIES RELATED TO AND COOLERS / FREEZERS INDICATED IN THESE DRAWINGS.
2. REFER TO THE "RESTROOM DESIGN CRITERIA" IN THE PROJECT MANUAL FOR ADDITIONAL INFORMATION REGARDING THE RESTROOM RENOVATION STANDARDS.
3. DO NOT SCALE THE DRAWINGS. REFER TO DIMENSIONS INDICATED ONLY IF FURTHER DIMENSIONAL INFORMATION IS REQUESTED, CONTACT THE ARCHITECT OR KROGER ENGINEER FOR CLARIFICATIONS.
4. PROVIDE WOOD BLOCKING IN STUD WALLS AS REQUIRED TO SUPPORT WALL MOUNTED EQUIPMENT AND SHELVING.
5. ALL ANGLED WALLS AND SOFFITS TO BE 45 DEGREES UNLESS NOTED OTHERWISE.
6. PROVIDE WOOD BLOCKING FOR SIGNAGE, COORDINATE LOCATION WITH KROGER ENGINEER.
7. THIS BUILDING CONTAINS A COMPLETE FIRE PROTECTION SYSTEM. NO EXPOSED PIPING SHALL BE ALLOWED IN THE FINISHED AREAS. SPRINKLER SYSTEM SHALL BE REVISED AS NECESSARY BY SPRINKLER CONTRACTOR'S CERTIFIED ENGINEER. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING ALL REQUIRED PERMITS FOR THIS WORK.
8. DIMENSIONS ARE TO FACE OF MASONRY WALL AT UNFINISHED MASONRY WALLS WITH FURRING AND GYPSUM BOARD WALLS. AT METAL STUD WALLS, DIMENSIONS ARE TO FINISHED FACE OF GYPSUM BOARD.
9. REFER TO FINISH PLAN AND SPECIFICATIONS FOR FINISHES. SUBMIT ALL FINISH SAMPLES TO KROGER ENGINEER FOR APPROVAL.
10. THE KROGER COMPANY WILL SUPPLY AND ERECT ALL EXTERIOR BUILDING SIGNAGE (IF APPLICABLE).
11. ADA ACCESSIBLE TOILET STALL DOORS TO BE A MINIMUM OF 2'-8" WIDE.
12. ALL WORK TO BE COORDINATED WITH KROGER ENGINEER AND RESPECTIVE TRADES.
13. ALL FRAMING LUMBER AND SHEATHING USED TO BE F.R.T. (FIRE RETARDANT TREATED).
14. USE CADMIUM PLATED OR STAINLESS STEEL SCREWS AND FASTENERS FOR F.R.T. WOOD. BACKER BOARDS, GREEN (MOISTURE RESISTANT) GYPSUM BOARD, EXTERIOR GYPSUM BOARD AND SHEATHING.
15. GYPSUM BOARD CONTROL JOINTS REQUIRED IN NEW SOFFITS AT 20'-0" O.C.. (LOCATE CONTROL JOINTS IN PAINTED SOFFITS ONLY. DO NOT LOCATE CONTROL JOINTS AT SIGNAGE AREAS.)
16. ALL WALLS TO BE INSTALLED TO BE 3-5/8" METAL STUD UNLESS OTHERWISE NOTED.
17. PROVIDE AND INSTALL DURROCK OR WONDER BOARD. BACK-UP TO 48" ABOVE FLOOR IN MEAT, SEAFOOD, PRODUCE PREP. AREAS, AND RESTROOMS AT ALL WALLS WITH CERAMIC TILES (EXCEPT ACCENT BAND). ALL OTHER AREAS IN RESTROOMS AND PREP ROOMS TO BE WATER RESISTANT GYPSUM BOARD.
18. DO NOT ATTACH METAL STUDS TO ROOF DECK. ATTACH METAL STUDS TO STRUCTURE AND EXTEND GYPSUM BOARD TO DECK.
19. ALL COLUMN DIMENSIONS ARE FROM EXISTING DRAWINGS. CONTRACTOR TO FIELD VERIFY ALL DIMENSIONS BEFORE START OF WORK.
20. FILL GAPS BETWEEN COOLERS, FREEZERS, AND ALL WALLS WITH MATERIALS TO MATCH ADJACENT SURFACES.
21. ALL COLUMNS TO BE PAINTED. IF CONTAINS A COLUMN COVER, THEN PAINT FROM TOP OF COLUMN COVER TO FINISHED CEILING. IF NO COLUMN COVER, THEN PAINT FROM FINISHED FLOOR TO FINISHED CEILING.
22. ALL COLUMN COVERS TO BE REPLACED BY G.C. PER DECOR PACKAGE STANDARDS. SEE ASD-63.
23. IF COLUMN BECOMES EXPOSED DUE TO THE NEW SHELVING LAYOUT THEN G.C. IS RESPONSIBLE FOR INSTALLING A NEW COLUMN COVER.
24. REMOVE EXISTING AND INSTALL NEW STRIP DOORS AT FREEZER/ COOLER LOCATIONS PER F1.
25. CONTRACTOR IS RESPONSIBLE FOR REPLACING ALL DRYWALL THAT IS DAMAGED BEHIND REPLACED CASES THAT HAS EITHER DETERIORATED OR SHOWS SIGNS OF MOLD.
26. 150 BASCARTS ARE TO BE ADDED. (G.C. IS RESPONSIBLE FOR UNLOADING.)
25. 75 URBAN CARTS ARE TO BE ADDED. (G.C. IS RESPONSIBLE FOR UNLOADING.)
26. 60 ELECTRICAL CARTS ARE TO BE ADDED. (G.C. IS RESPONSIBLE FOR UNLOADING.)
27. NEW KPNR, KBAR AND CENTER STORE IS TO BE INSTALLED. SEE PROJECT MANUAL FOR INSTALLATION GUIDELINES.
30. ALL EQUIPMENT ATTACHED TO WALLS RECEIVING NEW FINISHES NEED TO BE RELOCATED AND OPERATIONAL DURING THE INSTALLATION OF NEW WALL FINISHES.

Coded Notes

05A NEW REMOVABLE CHROME PROTECTIVE POST. COORDINATE LOCATIONS WITH FIXTURING CONTRACTOR AND KROGER ENGINEER. REFER TO ASD-19.
05B NEW ISLAND 24" CASE GUARDS. SEE ASD-160. COORDINATE LOCATIONS WITH FIXTURING CONTRACTOR & KROGER ENGINEER.
05C NEW GLASS DOOR 12" CASE GUARDS. SEE ASD-160A. COORDINATE LOCATIONS WITH FIXTURING CONTRACTOR & KROGER ENGINEER.
05D NEW SALES AREA COLUMN COVERS. REFER TO ASD-157
05E NEW STAINLESS STEEL COLUMN COVER. ASD-55A
05F NEW CONCRETE BOARD TO BE INSTALLED 4'-0" AFF. INSTALL MOISTURE BOARD FROM 4'-0" AFF TO 8" ABOVE CEILING IN MEAT SERVICE PREP AREA. PREP WALL FOR NEW CERAMIC TILE.

06A NEW PROTECTIVE WOOD BUMPER - SEE ASD-2
06B PROVIDE BLOCKING IN WALL AS REQUIRED FOR SINKS
06C STAINLESS STEEL WATER CUTOFF FLASHING AT PREP AREAS. REFER TO GISD-14.
06D NEW STAINLESS STEEL SHROUD TO BE INSTALLED ABOVE HOOD OF OVEN.
06E G.C. TO SEAL MANAGERS OFFICE WALL TO DECK FOR NOISE CANCELLATION.

08A NEW HOLLOW METAL DOOR AND FRAME. PAINT PER DOOR SCHEDULE
08B NEW DOUBLE ACTING DOOR AND FRAME PER ASD-56
08C NEW DOUBLE ACTING DOOR IN EXISTING STEEL FRAME (RIDGED DOOR)
08D NEW DOUBLE ACTING DOOR IN EXISTING STEEL FRAME (FLEXIBLE DOOR)
08E RELOCATED ALUMINUM ENTRANCE DOORS (BY KROGER)
08F FRAMED OPENING FOR HOT HOLD CABINET PASS THRU. 28"X 72" AFF

09A PAINT ENTIRE DOOR AND FRAME - SEE DOOR SCHEDULE FOR COLOR.
09B PAINT ENTIRE DOOR FRAME - SEE ROOM FINISH SCHEDULE FOR COLOR.
09C INSTALL NEW KROGER PROVIDED MILLWORK
09D PROVIDE / INSTALL NEW FILLER
09F INFILL EXISTING DOOR OPENING. SEE WALL TYPE
09G ELECTROSTATIC PAINT EXISTING COOLER. COLOR AS SELECTED BY KROGER ENGINEER.
09H G.C. TO REPAIR EXISTING PREP AREA WALLS.
09J NEW GYP BOARD TO BE INSTALLED. REFER TO DECOR DRAWINGS FOR FINISHES.

11A NEW TOILET PARTITION. REINSTALL SALVAGED ACCESSORIES
11B NEW MIRROR TO BE INSTALLED.
11C NEW TOP COLLAR TURNING POST. SEE ASD-20
11D NEW DIGITAL MENU BOARDS. REFER TO ASD-72
-INSTALLED 3' FROM THE BACK OF THE COUNTER (ASSOCIATE SIDE) OR ABOUT 5' FROM THE CUSTOMER SIDE OF THE COUNTER. REFER TO FINAL FIXTURE PLAN.
-TVS MUST BE INSTALLED WITH NO GAPS BETWEEN THE TVS, LEVEL, AND FLUSH WITH ONE ANOTHER ADHESIVE STRIPS MAY BE USED ON THE BACK OF THE PANELS FOR PROPER ALIGNMENT
-THE BOTTOM OF THE TV TO BE NO LESS THAN 60" FROM THE GROUND
-TIE POWER CORD TIGHT TO THE MOUNTING BRACKET
11E NEW STEEL CURTAIN TO BE INSTALLED

Legend

B	WALL TYPE MARK - SEE SHEET A5.1
X"	WALL STUD SIZE. ALL STUDS TO BE 3-5/8" UNLESS NOTED OTHERWISE.
XX'-XX"H WALL	PARTIAL WALL HEIGHT NOTED ON PLAN. REFER TO WALL TYPE ON A5.1 FOR DETAILS

#	Date	Change Description
1	01/02/20	ADDENDUM 001
2	01/09/20	ADDENDUM 002

KROGER N273
WORTHINGTON
60 WORTHINGTON MALL
WORTHINGTON, OH 43085
for
THE KROGER COMPANY

MOODY•NOLAN
300 Spruce Street
Suite 300
Columbus, Ohio 43215
Phone: (614) 461-4664
Fax: (614) 280-8881
www.moodynolan.com

STATE OF OHIO
CURTIS
ALLEN
REGISTERED ARCHITECT

Dwg. Coord.: NLF | Tech. Coord.: | Proj #: 19393

PLAN
NEW CONSTRUCTION

A1.1

BID/PERMIT SET | 12/10/2019

PLOTTED BY: $USER$
$DATE$ $TIME$ $FILE$