



General Walltype Notes

1. DEFLECTION TRACK TO BE USED AT BOTTOM OF JOISTS. CONSISTS OF 3" LONG LEG TO PROVIDE 1-1/2" OF VERTICAL MOVEMENT. DO NOT ATTACH METAL STUD WALL OR GYPSUM BOARD TO DEFLECTION TRACK. HOLD GYPSUM BOARD SHORT OF DECK BY 1-1/2".
2. GYPSUM BOARD: TYPICAL 1/2" GYP. BOARD USED UNLESS NOTED OTHERWISE. REMODEL PROJECTS USE 5/8" GYPSUM BOARD WHERE EXISTING 5/8" GYPSUM BOARD IS IN PLACE.
3. MOISTURE RESISTANT GYPSUM BOARD: 1/2" THICK UNLESS NOTED OTHERWISE.
4. CONCRETE BOARD: 1/2" UNLESS NOTED OTHERWISE.
5. METAL STUDS: STANDARD DEPTH TO BE 3/8" UNLESS NOTED OTHERWISE. REFER TO DETAILS FOR BRACING AND GAGE.
6. BRACING AT COOLER/FREEZER: FULL HEIGHT WALLS BUILT ALONG COOLER/FREEZER PANELS SHOULD BE BRACED AT ROOF PANEL TO UTILIZE STANDARD DEPTH METAL STUD.
7. GYPSUM BOARD AT PHARMACY GRILLE: INSTALL GYPSUM BOARD AS FAR AS POSSIBLE IN POCKET WALL FOR PHARMACY GRILLE. CONSIDER WHICH SIDE WILL BE VIEWED MOST BY CUSTOMERS WHEN INSTALLING GYPSUM BOARD.
8. FLOOR FINISH AND BASE: REFER TO INTERIOR DECOR PLANS & ROOM FINISH SCHEDULE. FOR WALL FINISHES REFER TO SPECIFICATION SECTIONS 1 AND 9.
9. FINISHED CEILINGS: EXTEND GYP. BD. 6" ABOVE CEILING. METAL STUDS DO NOT NEED TO EXTEND TO DECK (U.N.O.) IF BRACED BACK TO STRUCTURE ABOVE AT 48" O.C. MAX.
10. OSB WOOD PANEL ALLOWED FOR SB CONSTRUCTION. USE FRP WOOD PANEL FOR 2B NONCOMBUSTIBLE CONSTRUCTION.
11. ALL PARTITION WITH RECESSED ELECTRIC PANELS AND TOILET SHALL BE 6" STUD.
12. ALL PARTIAL HEIGHT WALLS IN SLUSH AND CHEESE SHOP LOCATIONS TO BE 48" AFF. OUTLETS FOR COUNTERTOP EQUIPMENT ARE TO BE INSTALLED ALONG WALLS ARE TO BE INSTALLED ABOVE TABLE SPALSH.

#	Date	Change Description

KROGER N273
WORTHINGTON
30 WORTHINGTON WALL
WORTHINGTON, OH 43085
for
THE KROGER COMPANY

MOODY•NOLAN
300 Spruce Street
Suite 300
Columbus, Ohio 43215
Phone: (614) 461-4664
Fax: (614) 280-8851
www.moodynolan.com

Dwg. Coord.: NLF	Tech. Coord.:	Proj #: 19393
DETAILS and INTERIOR WALLTYPES	A5.1	10/29/2019
95% OWNER REVIEW		