


FILE: L:\1663 (PROJECT KESPER, SITE 3, CITY OF NORTHVILLE)\C\6 PLANS\05-C1-5.DWG - PLOT DATE: 7/10/2015 4:50 PM BY: Michelle Shumaker SCALE: 1:1



- NOTES:**
1. INSTALL ALL SIGNS WHERE INDICATED ON SITE PLAN.
  2. ADJUST MOUNTING HEIGHTS TO MEET LOCAL CODES WHERE APPLICABLE.
  3. SET ALL POSTS IN 16" DIAMETER x 36" DEEP CONCRETE FOUNDATION.
  4. 4" x 6"-0" CONCRETE FILLED SCHEDULE 40 STEEL POST CENTERED IN FOUNDATION, PAINTED YELLOW, SEE SPECS.
  5. 2 1/4" WIDE x 6"-0" LONG U-CHANNEL POST WITH BAKED ON GREEN ENAMEL FINISH.
  6. LIGHT DUTY — LANDSCAPED AREAS AND AREAS NOT SUBJECT TO VEHICULAR TRAFFIC.  
HEAVY DUTY — PAVED AREAS AND AREAS SUBJECT TO VEHICULAR TRAFFIC OR NOT PROTECTED IN LANDSCAPED AREAS.

A  
C5.1

TRAFFIC CONTROL SIGNS

MASTER SPECIFICATION DETAIL CSD-60

B  
C5.1

PARKING STALL SIGNS

MASTER SPECIFICATION DETAIL CSD-61

C  
C5.1


PARKING LOT STRIPING DETAIL

MASTER SPECIFICATION DETAIL CSD-134

10/11/12

ZAW

CSD-134




NOTE:  
SYMBOL SHALL BE PAINTED BLUE  
AND TO THE DIMENSIONS SHOWN

PAINTED BARRIER-FREE  
PARKING SPACE SYMBOL DETAIL


(NOT TO SCALE)

F  
C5.1



ASPHALT PAVEMENT  
MILL & OVERLAY DETAIL


G  
C5.1



TYPICAL TRENCH DETAIL


UNDER ASPHALT SURFACES ONLY

H  
C5.1




CONCRETE ISLAND SECTION


J  
C5.1



- NOTES:**
1. DRIVE IMMEDIATELY IN FRONT OF STORE TO BE A MINIMUM OF 30'-0" WIDE.
  2. 10'-0" WIDE PARKING SPACE IS PREFERRED, 9'-0" OR ABSOLUTE MINIMUM 9'-0" WIDE MAY ONLY BE USED IF KROGER SPECIFICALLY APPROVES.
- ACCESSIBLE PARKING SPACES PER STATE AND LOCAL CODES:**
3. PARKING SPACES TO BE SIGNED WITH THE INTERNATIONAL SYMBOL OF ACCESSIBILITY. VAN SPACES SHALL HAVE ADDITIONAL VAN ACCESSIBLE SIGN MOUNTED BELOW THE SYMBOL. NO PARKING BLOCKS/BUMPERS. REFER TO CSD-61.
  4. ACCESSIBLE ROUTE WITH 3'-0" MIN. CLEAR WIDTH BETWEEN SIGN POSTS — EXCEPT CALIFORNIA TO BE 4'-0".



**ACCESSIBLE PARKING SPACES DESIGNS**  
--- VEHICLE STANDING SPACES AND ACCESS  
AISLES SHALL BE LEVEL WITH SURFACE SLOPES  
NOT EXCEEDING 2% IN ALL DIRECTIONS ---



PAINTED ARROW  
(YELLOW). SEE NOTE

PAINTED ARROW DETAIL

D  
C5.1



STOP


STOP & STOP BAR

PAINTING DETAIL

E  
C5.1

CLICKLIST

I  
C5.1



SECTION

CONCRETE SURFACE

(NOT TO SCALE)

K  
C5.1

**MISS DIG**

3 WORKING DAYS  
BEFORE YOU DIG  
OR DRILL  
CALL  
1-800-482-7171  
(TOLL FREE)

NO.	REVISIONS/SUBMITTALS
1	ISSUED FOR PERMIT
2	ISSUED FOR PERMIT
3	ISSUED FOR PERMIT
4	ISSUED FOR PERMIT
5	ISSUED FOR PERMIT
6	ISSUED FOR PERMIT
7	ISSUED FOR PERMIT
8	ISSUED FOR PERMIT
9	ISSUED FOR PERMIT
10	ISSUED FOR PERMIT

**LSG**  
Engineers  
& Surveyors

3135 PINE TREE ROAD  
SUITE D  
LANSING, MI 48911  
PH. (517) 393-2902  
FAX (517) 393-2608  
www.lsg-es.com

PREPARED FOR:

**Kroger**

THE KROGER CO.  
OF MICHIGAN  
40399 GRAND RIVER AVENUE,  
SUITE 110  
NOVI, MICHIGAN 48375

MISCELLANEOUS DETAILS  
FOR  
KROGER STORE D-361  
425 N. CENTER STREET  
NORTHVILLE, MICHIGAN

FILE	05_C1-5.DWG
DESIGNED BY	ADB
DRAWN BY	MLS
CHECKED BY	ADB
DATE	JUNE 16, 2015
SCALE	
HOR.	N/A
VERT.	N/A
PROJECT NO.	1663
SHEET NO.	C5.1