


- THIS PROJECT SHALL CONTAIN A COMPLETE FIRE PROTECTION SPRINKLER SYSTEM. THE FIRE SUPPRESSION, FIRE ALARM & THE BUILDING PREMISE/SECURITY ALARM DESIGN & DRAWINGS WILL BE BY OTHERS. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.
- SEE KROGER PROJECT MANAGER, SPECIFICATIONS, AND INTERIOR DECOR PLANS FOR PAINTING INSTRUCTIONS.
- COVER ALL FREESTANDING (SALES/PREP AREA) COLUMNS FROM FLOOR UP TO 5'-0" AFF SIMILAR TO ASD-63, SHEET A5.12. PAINT COLUMNS ABOVE COLUMN WRAP AND ALL COLUMNS THAT FALL WITHIN SHELVING OR CHASES PT-602 OR PER DECOR DRAWINGS. SEE GISD-20, SHEET A5.13, FOR COLUMNS THAT FALL WITHIN SHELVING. COLUMNS WITH-IN PREP AREAS TO BE STAINLESS STEEL FROM FLOOR TO CEILING. PROVIDE BOXED-IN COLUMNS OR CHASES AS REQUIRED & INDICATED, SEE DETAIL 521 ON SHEET A5.2.
- CONCRETE CURB. SEE ASD-6 & ASD-6A, SHEET A5.11. SEE CONCRETE PLAN ON SHEET A12.0.
- SEE GISD-16A ON SHEET A5.13 FOR SHELVING IN COOLERS & FREEZERS.
- PARTITIONS TO BOTTOM OF DECK OR JOIST AND PARTITIONS WITH RECESSED EQUIPMENT (ELECTRIC PANELS, FLY GRIDS, ETC.) OR PLUMBING FIXTURES SHALL BE 6" METAL STUDS.
- PROVIDE S.S. CORNER GUARD. SEE ASD-55A, SHEET A5.11.
- PROVIDE WOOD BLOCKING (INSERTED IN METAL STUDS) IN PARTITION THIS AREA, FOR SHELVING BRACKET SUPPORT (6'-0" TO 8'-0"), FOR BABY CHANGING STATION (FROM FLOOR TO 8'-0"), EXHAUST HOOD/STAINLESS STEEL (FROM FLOOR TO 9'-10") AND/OR FOR MISCELLANEOUS FIXTURES AND SHELVING AS REQUIRED. PATCH/REPAIR WALL & FINISHES AS REQUIRED WHEN ADDING BLOCKING TO EXISTING WALLS.
- MOUNTING HEIGHT FOR MISCELLANEOUS TOILET ROOM FIXTURES SHALL NOT EXCEED 3'-4" ABOVE FLOOR.
- SANITIZING PROPORTIONER. (BY KROGER)
 - 2-LEVER SPRAY DOWN PROPORTIONER (GE-235-2) WITH SANITIZER AND HOSE CABINET, GE183, (BY GC).
 - 3-LEVER SPRAY DOWN PROPORTIONER (GE-235-3).
 - 2-BUTTON PROPORTIONER FOR 3-COMPARTMENT SINKS (GE236-2C) OR MOP SINKS (GE236-2M).
 - SMALL 1-BUTTON PROPORTIONER (GE236S).
- REFRIGERATED CASE CORNER GUARD (SALES AREA) SEE SPECS. GUARD(S) TO BE SUPPLIED & INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET. SEE ASD-160 (ASD-160A FOR GLASS DOOR CASES) ON SHEET A5.12.
- PAINT EXISTING METAL DOORS & FRAMES, INSIDE & OUTSIDE. TYPICAL ALL EXISTING DOORS. NEW DOORS & FRAMES TO BE PAINTED PER SPECIFICATIONS. OUTSIDE FACE OF EXTERIOR DOORS TO BE PAINTED TO MATCH ADJACENT BUILDING MATERIALS OR TO MATCH EXISTING DOORS.
- REMOVABLE PROTECTIVE POST(S) (SALES AREA), SEE SPECS. POST(S) TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET.
- PROVIDE BACKER ROD AND SEALANT BETWEEN WALL AND INSULATED PANEL. SEALANT TO MATCH COOLER WALL, FOR 1" SPACE OR LESS. PROVIDE INFILL WITH STUD, GYPSUM BOARD, & APPROPRIATE WALL FINISH OVER EXPOSED AIR SPACE GREATER THAN 1" BETWEEN INSULATED PANELS & WALL COMBINATIONS. PROVIDE AIR TIGHT INFILL BETWEEN WALLS, COOLERS, OR FREEZERS AND NEW INSULATED PANELS AT THE SIDES & ABOVE OPENINGS IN THE INSULATED PANELS.
- COLUMN "PRICE CHECKER". SEE ELECTRICAL DRAWINGS AND ESD-55, E5.12 FOR MOUNTING & CONNECTION DETAILS.
- PROVIDE AND INSTALL VERTICAL AIR CURTAIN STRIPS ON INSIDE OF DOORWAYS WHERE INDICATED.
- MODIFY WALL, PATCH & REPAIR AS REQUIRED FOR NEW REFRIGERATION LINES. COORDINATE LOCATION WITH REFRIGERATION TRADES. SEE DETAIL 532, SHEET A5.2.
- PROVIDE ALL NEW SUBSTRATE AND PREP TO RECEIVE NEW FINISHES AS REQUIRED DUE TO REMOVAL OF ALL EXISTING FINISHES. SUBSTRATE TO BE CEMENT BOARD TO 48" AFF & MOISTURE RESISTANT GYPSUM BOARD TO CEILING AT PREP AREAS AND RESTROOMS (AT NEW WALL TILE & FRP). PROVIDE NEW GYPSUM BOARD AT ALL OTHER AREAS AS REQUIRED. PROVIDE A CLEAN FLUSH SURFACE TO APPLY NEW WALL FINISH AS INDICATED.
- CLEANING STATION W/ RECESSED (WHERE POSSIBLE) SANITIZER CABINET (BY GC) & 2-LEVER SPRAY DOWN PROPORTIONER (BY KROGER) . SEE DETAIL 531, SHEET A5.2.

- SEE GENERAL NOTES ON SHEET A11.0
- SEE SHEET A11.4 FOR DECOR, MILLWORK, & FIXTURE / CASE NOTES.



431

PRODUCE & BAKERY PREP
ENLARGED PLAN

SCALE: 1/4" = 1'-0"

ADDENDUM NO. 3
BIDS & PERMITS
80% OWNER REVIEW

07-18-2015
06-28-2015
06-22-2015

PROPOSED INTERIOR REMODEL FOR:



STORE NO. D-361

425 N. CENTER STREET
NORTHVILLE, MI 48167

THE KROGER CO. OF MICHIGAN



jeffery a.
scott
architects p.c.

32316 grand river ave. suite 200
farmington, michigan 48336-3261
(248) 476-8800 fax (248) 476-8833

ENLARGED PLANS & DETAILS

project no.
15100

sheet no.
A4.3

plot full size @ 30"x42"
copyright © 2015