

## FLOOR COVERING SCHEDULE


### NEIGHBORHOOD DECOR

SEE THE USA CONSTRUCTION DRAWINGS (ARCHITECTURAL & INTERIORS), PROJECT SPECIFICATIONS SECTION 01 61 12 "GENERAL INTERIOR FINISHES AND COLORS" AND DECOR DOCUMENTS BY OTHERS FOR INFORMATION ON THE FINISHES AND DECOR. COORDINATE EXTENT OF DECOR WORK WITH KROGER ENGINEER & THE DECOR DRAWINGS BY OTHERS.

BELOW ARE FINISH ITEMS THAT ARE NOT IN THE SPECIFICATIONS.

AREA	DWG. REF.	MAN.	PATTERN	NUMBER	COLOR	SIZE	PURCHASED/INSTALLED
	SC	NEW SEALED CONCRETE	EXPOSED GRAY CONCRETE	-	ANTI-SLIP W/ SEALER	-	G.C./G.C.
	CT-N2	DALTILE	FABRIQUE	#P690	GRIS LINEN (UNPOLISHED)	12"x24"	G.C./G.C.
	CP-N	MOHAWK	RENEGADE	#358	THRILL SEEKER	24" x 24"	G.C./G.C.
	CP-603	PORTICO SYSTEMS	ENTRANCE FLOORING	-	DOMINATOR, HEATH	-	G.C./G.C.
	VT-01	ARMSTRONG	VCT	#T3612	STARBUST	-	G.C./G.C.
	VT-02	ARMSTRONG	LVT	#TP063	DRIFTWOOD BRONZE	-	G.C./G.C.
	WB-N	JOHNSONITE	RUBBER COVE BASE	#80	FAWN	-	G.C./G.C.
	EXIST	-	EXISTING	-	EXISTING	-	-

### FLOOR COVERING KEY



### GENERAL NOTES AND SPECIFICATIONS

- ALL TILES TO BE PER SPECIFICATIONS UNLESS NOTED OTHERWISE. IF CUTTING TILE IS NECESSARY, NO TILE SHALL BE LESS THAN 4" EXCEPT AT WALLS.
- TILE GRAIN TO RUN IN SINGLE DIRECTION UNLESS OTHERWISE NOTED, RUN GRAIN FRONT TO BACK. IF TILE IS INSTALLED AT 45 DEGREES, RUN GRAIN FROM SOUTHEAST TO NORTHWEST.
- WHERE TWO TILE THICKNESSES ADJOIN - PROVIDE TRANSITION AS REQUIRED TO PRODUCE FLUSH JOINT.
- ALL EXPOSED WALLS TO RECEIVE NEW VINYL WALL BASE TO BE PER SPECIFICATIONS UNLESS OTHERWISE NOTED.
- VERIFY ALL FLOOR FINISHES W/LOCAL HEALTH DEPARTMENT BEFORE PROCEEDING
- VERIFY ALL TILE ALIGNMENTS PER PLAN WITH FIXTURE LOCATIONS & DIMENSIONS PRIOR TO STARTING WORK.
- WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALE.
- ANY DISCREPANCIES W/OOB SITE CONDITIONS CONTACT ARCHITECT/KROGER ENGINEER BEFORE PROCEEDING.
- FLOOR FINISH MUST EXTEND A MINIMUM 6'-0" PAST SALES FLOOR DOORS INTO BACKROOM AREAS.
- GEN. SALES FLOOR FINISH TO CARRY UNDERNEATH THE CASES, SHELVING & FIXTURES. CARRY CONTINUOUS TO PERIMETER INTERIOR/BLDG. WALLS, UNLESS NOTED OTHERWISE.
- SEE MANUFACTURER'S SPECIFICATIONS FOR INSTALLATION REQUIREMENTS OF FINISHES SPECIFIED IN THESE DRAWINGS.
- PROVIDE PROPER AND REQUIRED VENTILATION FOR INSTALLATION OF ALL RESINOUS FLOORING.
- THE CONTRACTOR WILL NEED TO WALK THE STORE PRIOR TO BIDDING TO VERIFY ANY DAMAGED OR PROBLEMATIC AREAS THAT NEED TO BE REPAIRED DURING CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR ALL FLOOR PREP PRIOR TO INSTALLING NEW FLOOR FINISHES.

### FLOORING NOTES

- FIELD CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS PRIOR TO STARTING WORK.
- CONTACT KROGER ENGINEER (PRIOR TO PLACEMENT OF ANY RESILIENT FLOOR COVERING) TO VERIFY CONFORMANCE W/ FINAL FLOOR COVERING PLAN AND LATEST MARKETING AREA FIXTURE PLAN.
- ALL VCT & LVT (FAUX WOOD VINYL PLANK) FLOORING IS NOT A DIRECT BUY ITEM AND WILL BE PROVIDED BY THE G.C. ADHESIVE FOR VCT & LVT FLOORING WILL BE PROVIDED BY THE G.C.
- PAINT FIRE EXIT LANES AT BACKROOM AREAS. (TYPICAL LANES ARE A PAINTED BORDER STRIPE EACH SIDE OF LANE. BORDER STRIPE TO BE 3" WIDE AND SPACED 44" APART AT THE OUTSIDE DIMENSIONS.)
- INSTALL NEW FLOOR FINISH AFTER ALL SAW CUT AREAS, TRENCHES & PITS AND OTHER WORK HAS BEEN INSTALLED AND TESTED AND CONCRETE HAS CURED.
- PATCH AND REPAIR ANY DAMAGED CONCRETE FLOOR AS REQUIRED FOR NEW FLOOR FINISHES. MATCH & ALIGN WITH ADJACENT FLOOR FINISH.
- G.C. TO PROVIDE ALL NECESSARY FLOOR PREP PRIOR TO INSTALLING NEW FLOOR FINISHES. THIS INCLUDES THE ADJUSTING OF ALL FLOOR DRAINS, CLEANOUTS, ACCESS PLATES, ROSE BBS, ELECTRICAL OUTLETS, & OTHER FLOOR MOUNTED ITEMS DUE TO NEW FLOOR FINISH.
- FOR WALL TO FLOOR BASE TYPES SEE ASD-51A TO ASD-51E ON SHEET A5.11.
- PAINT 8" STRIPE ON FLOOR AGAINST WALL AND 8" STRIPE ON WALL FROM FLOOR (EXCEPT ON COOLER WALLS) WITH SEMI-GLOSS WHITE PAINT IN THE STAGING AREA AND DOCK. SEE SPECS.
- NEW VCT/LVT FLOORING AT PRODUCE CASES WITH MISTING SYSTEM AND SEAFOOD SERVICE CASES SHALL HAVE A 2-PART EPOXY TYPE ADHESIVE. EPOXY ADHESIVE SHALL BE UTILIZED UP TO 10'-0" OUT FROM WALL OR REAR OF CASE. SEE SPECIFICATIONS.

BULLETIN NO. 2  
ADDENDUM NO. 1  
BIDS & PERMITS  
80% OWNER REVIEW  
08-17-2016  
07-10-2016  
08-28-2016  
08-22-2016

ISSUED FOR:  
PROPOSED INTERIOR REMODEL FOR:



STORE NO. D-361

425 N. CENTER STREET  
NORTHVILLE, MI 48167

THE KROGER CO. OF MICHIGAN

**jeffery a. scott architects p.c.**

32316 grand river ave. suite 200  
farmington, michigan 48336-3261  
(248) 476-8800 fax (248) 476-8833

FLOOR FINISH PLAN



project no.

15100

sheet no.

A1.6



copyright © 2016



## MEZZANINE PLAN

SCALE: 3/32" = 1'-0"

NOTE:  
COORDINATE ALL FINISHES WITH  
"NEIGHBORHOOD DECOR FINISHES\_06-22-15  
R4.PDF" & "KROGER\_#361 NORTHVILLE  
DECOR PACKAGE\_7.8.15.PDF"



## FLOOR FINISH PLAN

SCALE: 3/32" = 1'-0"