


1. THIS PROJECT SHALL CONTAIN A COMPLETE FIRE PROTECTION SPRINKLER SYSTEM. THE FIRE SUPPRESSION, FIRE ALARM & THE BUILDING PREMISE/SECURITY ALARM DESIGN & DRAWINGS WILL BE BY OTHERS. SEE SPECIFICATIONS FOR ADDITIONAL INFORMATION.
2. SEE KROGER PROJECT MANAGER, SPECIFICATIONS, AND INTERIOR DECOR PLANS FOR PAINTING INSTRUCTIONS.
3. COVER ALL FREESTANDING (SALES/PREP AREA) COLUMNS FROM FLOOR UP TO 8'-0" AFF SIMILAR TO ASD-63, SHEET A5.12. PAINT COLUMNS ABOVE COLUMN WRAP AND ALL COLUMNS THAT FALL WITHIN SHELVING OR CASES PT-602 OR PER DECOR DRAWINGS. SEE GISD-50, SHEET A5.13, FOR COLUMNS THAT FALL WITHIN SHELVING. COLUMNS WITH-IN PREP AREAS TO BE STAINLESS STEEL FROM FLOOR TO CEILING. PROVIDE BOXED-IN COLUMNS OR CHASES AS REQUIRED & INDICATED, SEE DETAIL 521 ON SHEET A5.2.
4. CONCRETE CURB. SEE ASD-6 & ASD-6A, SHEET A5.11. SEE CONCRETE PLAN ON SHEET A12.0.
5. SEE GISD-16A ON SHEET A5.13 FOR SHELVING IN COOLERS & FREEZERS.
6. PARTITIONS TO BOTTOM OF DECK OR JOIST AND PARTITIONS WITH RECESSED EQUIPMENT (ELECTRIC PANELS, FLY GRIDS, ETC.) OR PLUMBING FIXTURES SHALL BE 6" METAL STUDS.
7. PROVIDE S.S. CORNER GUARD. SEE ASD-55A, SHEET A5.11.
8. PROVIDE WOOD BLOCKING (INSERTED IN METAL STUDS) IN PARTITION THIS AREA, FOR SHELVING BRACKET SUPPORT (6'-0" TO 9'-0"), FOR BABY CHANGING STATION (FROM FLOOR TO 8'-0"), EXHAUST HOOD/STAINLESS STEEL (FROM FLOOR TO 9'-10") AND/OR FOR MISCELLANEOUS FIXTURES AND SHELVING AS REQUIRED. PATCH/REPAIR WALL & FINISHES AS REQUIRED WHEN ADDING BLOCKING TO EXISTING WALLS.
9. MOUNTING HEIGHT FOR MISCELLANEOUS TOILET ROOM FIXTURES SHALL NOT EXCEED 3'-4" ABOVE FLOOR.
10. SANITIZING PROPORTIONER. (BY KROGER)  
a. 2-LEVER SPRAY DOWN PROPORTIONER (GE-235-2) WITH SANITIZER AND HOSE CABINET, GE183, (BY GC).  
b. 3-LEVER SPRAY DOWN PROPORTIONER (GE-235-3).  
c. 2-BUTTON PROPORTIONER FOR 3-COMPARTMENT SINKS (GE236-2C) OR MOP SINKS (GE236-2M).  
d. SMALL 1-BUTTON PROPORTIONER (GE236S)
11. REFRIGERATED CASE CORNER GUARD (SALES AREA), SEE SPECS. GUARD(S) TO BE SUPPLIED & INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET. SEE ASD-160 (ASD-160A FOR GLASS DOOR CASES) ON SHEET A5.12.
12. PAINT EXISTING METAL DOORS & FRAMES, INSIDE & OUTSIDE. TYPICAL ALL EXISTING DOORS. NEW DOORS & FRAMES TO BE PAINTED PER SPECIFICATIONS. OUTSIDE FACE OF EXTERIOR DOORS TO BE PAINTED TO MATCH ADJACENT BUILDING MATERIALS OR TO MATCH EXISTING DOORS.
13. REMOVABLE PROTECTIVE POST(S) (SALES AREA), SEE SPECS. POST(S) TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET.
14. PROVIDE BACKER ROD AND SEALANT BETWEEN WALL AND INSULATED PANEL. SEALANT TO MATCH COOLER WALL. FOR 1" SPACE OR LESS. PROVIDE INFILL WITH STUD, GYPSUM BOARD, & APPROPRIATE WALL FINISH OVER EXPOSED AIR SPACE GREATER THAN 1" BETWEEN INSULATED PANELS & WALL COMBINATIONS. PROVIDE AIR TIGHT INFILL BETWEEN WALLS, COOLERS, OR FREEZERS AND NEW INSULATED PANELS AT THE SIDES & ABOVE OPENINGS IN THE INSULATED PANELS.
15. COLUMN "PRICE CHECKER". SEE ELECTRICAL DRAWINGS AND E5D-55, E5.12 FOR MOUNTING & CONNECTION DETAILS.
16. PROVIDE AND INSTALL VERTICAL AIR CURTAIN STRIPS ON INSIDE OF DOORWAYS WHERE INDICATED.
17. MODIFY WALL, PATCH & REPAIR AS REQUIRED FOR NEW REFRIGERATION LINES. COORDINATE LOCATION WITH REFRIGERATION TRADES. SEE DETAIL 532, SHEET A5.2.
18. PROVIDE ALL NEW SUBSTRATE AND PREP TO RECEIVE NEW FINISHES AS REQUIRED DUE TO REMOVAL OF ALL EXISTING FINISHES. SUBSTRATE TO BE CEMENT BOARD TO 48" AFF & MOISTURE RESISTANT GYPSUM BOARD TO CEILING AT PREP AREAS AND RESTROOMS (AT NEW WALL TILE & FRP). PROVIDE NEW GYPSUM BOARD AT ALL OTHER AREAS AS REQUIRED. PROVIDE A CLEAN FLUSH SURFACE TO APPLY NEW WALL FINISH AS INDICATED.
19. CLEANING STATION W/ RECESSED (WHERE POSSIBLE) SANITIZER CABINET (BY GC) & 2-LEVER SPRAY DOWN PROPORTIONER (BY KROGER) . SEE DETAIL 531, SHEET A5.2.

- SEE GENERAL NOTES ON SHEET A11.0
- SEE SHEET A11.4 FOR DECOR, MILLWORK & FIXTURE / CASE NOTES.



NOTE:  
TOMRA ROOM TO BE 1/2" M.R. GYPSUM BOARD. PROVIDE CEMENT BOARD TO 4'-0" AFF BEHIND THE FRP. FRP TO OCCUR BEHIND TOMRA UNITS AND TO 6'-0" AFF.

441

RECYCLING & DELI PREP  
ENLARGED PLAN

SCALE: 1/4" = 1'-0"

BULLETIN NO. 2  
ADDENDUM NO. 3  
ADDENDUM NO. 1  
BIDS & PERMITS  
80% OWNER REVIEW

08-17-2015  
07-16-2015  
07-16-2015  
06-28-2015  
06-22-2015

PROPOSED INTERIOR REMODEL FOR:



STORE NO. D-361

425 N. CENTER STREET  
NORTHVILLE, MI 48167

THE KROGER CO. OF MICHIGAN

jeffery a.  
scott  
architects p.c.

32316 grand river ave. suite 200  
farmington, michigan 48336-3261  
(248) 476-8800 fax (248) 476-8833

ENLARGED PLANS & DETAILS

project no.

15100

sheet no.

A4.4