

UNDERSIDE SHELF VIEW



SECTION DETAIL

NOTES:

1. CUT OPENING FOR COLUMN AS TIGHT AS POSSIBLE. 1/4" GAP MAXIMUM.
2. INSTALL STANDARD BETWEEN SHELVING RIBS. STANDARD LOCATIONS MAY VARY BASED ON SHELVING CUT OPENINGS AND COLUMN POSITIONS.
3. SUPPORT RIB LOCATION VARIES BY MANUFACTURER AND SHELF DEPTH.

CUT SHELVING SUPPORT DETAIL	DATE: 7/23/12 SCALE: NONE DRAWN: ZAW
MASTER SPECIFICATION DETAIL	GISD-50

ORIGINAL ISSUE DATE 7/23/12



CASE FLASHING DETAIL



OUTSIDE CORNER DETAIL



S.S. WATER CUT OFF FLASHING FABRICATION DETAIL

NOTES:

1. FOR CASES THAT DO NOT HAVE A REMOVABLE REAR CASE TRIM, ATTACH THE FLASHING TO THE BACK OF THE CASE AND CAULK ALONG THE TOP.
2. GC TO PROVIDE "TRIM-LOK X2828BT" EPDM SPONGE-RUBBER D-SHAPED SEAL AND DOUBLE-SIDED 3M BONDED TAPE SYSTEM TO ADHERE TO FLASHING
3. WHERE FLASHING PIECES BUTT TOGETHER CAULK JOINT WITH SILVER SILICONE ENTIRE LENGTH OF JOINT EXPOSED.
4. ENSURE GOOD COMPRESSION OF RUBBER SEAL TO THE FLOOR FOR WATER-TIGHT FUNCTION
5. ENSURE BREAKS BETWEEN SECTIONS OR CUT OUT SECTIONS TO PROVIDE ACCESS TO ANY CONTROLS AT THE BOTTOM OF THE CASES

STAINLESS STEEL WATER CUT OFF FLASHING	DATE: 12/02/21 SCALE: NONE DRAWN: JDB
MASTER SPECIFICATION DETAIL	GISD-14

ORIGINAL ISSUE DATE 10/11/12



NOTES:

1. THE CONTRACTOR(S) ARE RESPONSIBLE FOR ALL MEANS AND METHODS TO DESIGN AND INSTALL TEMPORARY COVERS FOR TRENCHES, HOLES, ETC. TO ENSURE STABILITY/STRUCTURAL INTEGRITY. PROVIDE A SAFE SURFACE FOR THE APPLICABLE USES WITHOUT ALLOWING BOWING OR DEFLECTION AND MINIMIZE GAPS. REDUCING TRIP HAZARDS BY LEAVING FLUSH EDGES. TEMPORARY COVERS SECURELY IN PLACE AND HIGHLIGHTING TRANSITIONS WITH TAPE (CONTRASTING COLOR TO FLOOR) IS CRITICAL.
2. COORDINATE TRENCH CUTS WITH SAW CUTTING VENDOR TO ENSURE STRAIGHT AND SQUARE LINES WITHOUT CROSS CUTTING OR OVERCUTS.
3. ALTERNATE: STEEL PLATES EXTENDING BEYOND THE TRENCH CAN BE USED. PROVIDE A SAFE SURFACE FOR THE APPLICABLE USES WITHOUT ALLOWING BOWING OR DEFLECTION. REDUCING TRIP HAZARDS BY COVERING STEEL PLATE WITH BLACK MATS. HIGHLIGHTING TRANSITIONS WITH TAPE (COLOR CONTRASTING TO THE FLOOR) IS CRITICAL. REVIEW THIS METHOD WITH KROGER PROJECT MANAGER FOR APPROVAL PRIOR TO USE.

TEMPORARY COVER FOR FLOOR SLAB TRENCHES	DATE: 9/9/22 SCALE: NONE DRAWN: JDB
MASTER SPECIFICATION DETAIL	ASD-162D

ORIGINAL ISSUE DATE 09/09/22



DETAIL 'A'



TYPE - 1
WITH-IN WALL REMODEL
WITH SHELVING

TYPE - 2
WITH-IN WALL REMODEL
WITH-OUT SHELVING

NOTES:

1. 6 MIL FIRE RETARDANT (NFPA 701) POLYETHYLENE SHEETING DUST BARRIER — USE WHITE, CLEAR OR FROSTED/TRANSLUCENT SHEETING ONLY. BLACK SHEETING IS NOT ACCEPTABLE. TAPE FULL LENGTH OF JOINT, SECURELY ATTACH TO EITHER BACK OF SHELVING OR 2" x 4" WOOD BRACE BARRICADE, AND EXTEND UP TO ROOF DECK AS INDICATED.
2. 2" x 4" WOOD BRACED BARRICADE 8'-0" HIGH, PROVIDE BALLAST ON BOTTOM BRACE TO SECURE BARRICADE IN PLACE. DO NOT NAIL TO FLOOR. (BALLAST — i.e. - CONCRETE BLOCKS, SANDBAGS or MISCELLANEOUS CONSTRUCTION MATERIALS). BALLAST & KICKERS SHALL BE ON THE WORK AREA SIDE AND NOT ON THE CUSTOMER ACCESS SIDE.
3. ANY PORTION OF THE SPRINKLER SYSTEM WHICH BECOMES EXPOSED TO POSSIBLE FREEZING TEMPERATURES MUST BE PROTECTED FROM FREEZING WITH HEAT TAPE & INSULATION.

TEMPORARY CONSTRUCTION BARRIERS	DATE: 7/31/19 SCALE: NONE DRAWN: DS/JG/ZW
MASTER SPECIFICATION DETAIL	ASD-162A

ORIGINAL ISSUE DATE 6/1/07



NOTES

1. ALL CHANNEL IS COOPER B-LINE STRUT SYSTEMS B22SH SLOTTED CHANNEL.
2. COOPER B-LINE STRUT SYSTEMS B133 FOUR HOLE TEE PLATE.
3. COOPER B-LINE STRUT SYSTEMS B357 FOUR HOLE OFFSET BENT TEE PLATE.
4. IF THREADED RODS ARE NOT FULL LENGTH USE JAMB NUTS ON BOTH SIDES OF COUPLER.
4. IF THREADED RODS CANNOT BE CONNECTED AT BAR JOIST TOP CHORD, SPAN (3) BAR JOISTS WITH STRUT CHANNEL.
5. ADJUST ANGLE OF MONITOR FOR BEST VIEW OF DISPLAY.
6. ATTACHMENTS CAN BE MADE TO EITHER TOP CHORD OF JOIST OR UNISTRUT CHANNEL. ATTACHMENTS TO BOTTOM CHORD OF JOISTS TO ROOF METAL DECKING WILL NOT BE PERMITTED
7. IN STORES WITH LOWER CEILING PLEASE CO-ORDINATE WITH G.C. INTERIORS GROUP.

K-0056897 48" MONITOR
K-0053658 MOUNTING KIT

DELI MONITOR MOUNTING (8FT. DROP PARTITION)	DATE: 11/29/17 SCALE: NONE DRAWN: TMW
MASTER SPECIFICATION DETAIL	ASD-72A

ORIGINAL ISSUE DATE 11/29/17

- FOR REFERENCE ONLY -

issued for: BIDS AND PERMITS 03/13/2024
90% OWNER REVIEW 02/08/2024

PROPOSED MINOR INTERIOR REMODEL FOR:

Kroger

STORE NO. D-365

3615 WASHTENAW AVE
ANN ARBOR, MI 48104

THE KROGER CO. OF MICHIGAN

jeffery a. scott architects p.c.
32316 grand river ave. suite 200
farmington, michigan 48336-3261
(248) 476-8800 fax (248) 476-8833

KROGER ASDs GISDs & GIDs

project no. 23058

sheet no. A5.1.2

PLOT FULL SIZE @ 30"x42"

copyright © 2024