

NOTES:

1. FOR CASES THAT DO NOT HAVE A REMOVABLE REAR CASE TRIM, ATTACH THE FLASHING TO THE BACK OF THE CASE AND CAULK ALONG THE TOP.
2. GC TO PROVIDE "TRIM-LOK X2828BT" EPDM SPONGE-RUBBER D-SHAPED SEAL AND DOUBLE-SIDED 3M BONDED TAPE SYSTEM TO ADHERE TO FLASHING
3. WHERE FLASHING PIECES BUTT TOGETHER CAULK JOINT WITH SILVER SILICONE ENTIRE LENGTH OF JOINT EXPOSED.
4. ENSURE GOOD COMPRESSION OF RUBBER SEAL TO THE FLOOR FOR WATER-TIGHT FUNCTION
5. ENSURE BREAKS BETWEEN SECTIONS OR CUT OUT SECTIONS TO PROVIDE ACCESS TO ANY CONTROLS AT THE BOTTOM OF THE CASES

STAINLESS STEEL WATER CUT OFF FLASHING	DATE: 12/02/21 SCALE: NONE DRAWN: JDB
MASTER SPECIFICATION DETAIL	GISD-14

ORIGINAL ISSUE DATE 10/11/12



NOTES:

1. THE CONTRACTOR(S) ARE RESPONSIBLE FOR ALL MEANS AND METHODS TO DESIGN AND INSTALL TEMPORARY COVERS FOR TRENCHES, HOLES, ETC. TO ENSURE STABILITY/STRUCTURAL INTEGRITY. PROVIDE A SAFE SURFACE FOR THE APPLICABLE USES WITHOUT ALLOWING BOWING OR DEFLECTION AND MINIMIZE GAPS, REDUCING TRIP HAZARDS BY LEAVING FLUSH EDGES. FASTENING COVERS SECURELY IN PLACE AND HIGHLIGHTING TRANSITIONS WITH TAPE (CONTRASTING COLOR TO FLOOR) IS CRITICAL.
2. COORDINATE TRENCH CUTS WITH SAW CUTTING VENDOR TO ENSURE STRAIGHT AND SQUARE LINES WITHOUT CROSS CUTTING OR OVERCUTS.
3. ALTERNATE: STEEL PLATES EXTENDING BEYOND THE TRENCH CAN BE USED. PROVIDE A SAFE SURFACE FOR THE APPLICABLE USES WITHOUT ALLOWING BOWING OR DEFLECTION. REDUCING TRIP HAZARDS BY COVERING STEEL PLATE WITH BLACK MATS, HIGHLIGHTING TRANSITIONS WITH TAPE (COLOR CONTRASTING TO THE FLOOR) IS CRITICAL. REVIEW THIS METHOD WITH KROGER PROJECT MANAGER FOR APPROVAL PRIOR TO USE.

TEMPORARY COVER FOR FLOOR SLAB TRENCHES	DATE: 9/9/22 SCALE: NONE DRAWN: JDB
MASTER SPECIFICATION DETAIL	ASD-162D

ORIGINAL ISSUE DATE 09/09/22



NOTES:

1. 6 MIL FIRE RETARDANT (NFPA 701) POLYETHYLENE SHEETING DUST BARRIER -- USE WHITE, CLEAR OR FROSTED/TRANSLUCENT SHEETING ONLY, BLACK SHEETING IS NOT ACCEPTABLE. TAPE FULL LENGTH OF JOINT, SECURELY ATTACH TO EITHER BACK OF SHELVING OR 2" x 4" WOOD BRACE BARRICADE, AND EXTEND UP TO ROOF DECK AS INDICATED.
2. 2" x 4" WOOD BRACED BARRICADE 8'-0" HIGH, PROVIDE BALLAST ON BOTTOM BRACE TO SECURE BARRICADE IN PLACE, DO NOT NAIL TO FLOOR, (BALLAST -- i.e. - CONCRETE BLOCKS, SANDBAGS or MISCELLANEOUS CONSTRUCTION MATERIALS). BALLAST & KICKERS SHALL BE ON THE WORK AREA SIDE AND NOT ON THE CUSTOMER ACCESS SIDE.
3. ANY PORTION OF THE SPRINKLER SYSTEM WHICH BECOMES EXPOSED TO POSSIBLE FREEZING TEMPERATURES MUST BE PROTECTED FROM FREEZING WITH HEAT TAPE & INSULATION.

TEMPORARY CONSTRUCTION BARRIERS	DATE: 7/31/19 SCALE: NONE DRAWN: DS/JD/ZW
MASTER SPECIFICATION DETAIL	ASD-162A

ORIGINAL ISSUE DATE 6/1/07



NOTES:

1. DESIGNED FOR USE WITH GLASS DOOR END CASES. CASE CORNER GUARD; REFER TO SECTION 11 41 13 PARAGRAPH 2.2 B GENERAL STORE FIXTURE INSTALLATION IN SPECIFICATIONS. REFER TO FIXTURE PLAN FOR QUANTITY AND LOCATIONS.
2. CASE CORNER GUARD TO BE INSTALLED, AFTER CASE HAS BEEN SET. INSTALL CASE GUARD AS CLOSE TO CASE AS POSSIBLE PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.

Note:
Detail Based On Installation Instructions From National Cart Co. 5050001.
Legend Number GE63CS. Height 12".

GLASS DOOR END CASE CORNER GUARD	DATE: 6/5/15 SCALE: NONE DRAWN: ZAW
MASTER SPECIFICATION DETAIL	ASD-160A

ORIGINAL ISSUE DATE 6/5/15



NOTES:

1. DESIGNED FOR USE WITH ISLAND REFRIGERATED CASES (WITH STRAIGHT FRONTS) IN DAIRY, MEAT, SEAFOOD AND DELI DEPARTMENTS. CASE CORNER GUARD; REFER TO SECTION 11 41 13 PARAGRAPH 2.2 B GENERAL STORE FIXTURE INSTALLATION IN SPECIFICATIONS. REFER TO FIXTURE PLAN FOR QUANTITY AND LOCATIONS.
2. CASE CORNER GUARD TO BE INSTALLED, AFTER CASE HAS BEEN SET. INSTALL CASE GUARD (AND FLANGE EXTENSION) AS CLOSE TO CASE AS POSSIBLE PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.
3. MAXIMUM 1" PER MANUFACTURER'S INSTALLATION INSTRUCTIONS.
4. FOR CASES WITH SHALLOW TOE KICK IT MAY BE NECESSARY TO FIELD CUT FLANGE FOR PROPER POSITIONING OF GUARD.

Note:
Detail Based On Installation From National Cart Co. 6505001 (5050009 And 5050010).

REFRIGERATED CASE CORNER GUARD	DATE: 6/5/15 SCALE: NONE DRAWN: ZAW
MASTER SPECIFICATION DETAIL	ASD-160

ORIGINAL ISSUE DATE 7/6/06



NOTE:

1. DOCK TRUCK UNLOADING LIGHT, SEE ASD-62, ASD-62A AND FIXTURE PLAN.
2. INSTALL DOOR PROTECTORS AT DOOK DOOR WITH LEVELER.
3. RECOMMENDED WIDTH CLEARANCE BETWEEN TRUCKS AND ADJACENT WALLS.

Detail Based on:
Curtlap UDP by McGee Corporation
For 8' - 9" Wide Doors Part No. CSLDP-KIT

DOCK DOORS INSTALLATION	DATE: 1/30/15 SCALE: NONE DRAWN: ZAW
MASTER SPECIFICATION DETAIL	ASD-152

ORIGINAL ISSUE DATE 2/20/06

- FOR REFERENCE ONLY -

BIDS AND PERMITS 04/15/2024
issued for: 90% OWNER REVIEW 03/07/2024

PROPOSED MINOR INTERIOR REMODEL FOR:

Kroger — Here for Everyone

STORE NO. D-406
1200 E BRISTOL RD
BURTON, MI 48529

THE KROGER CO. OF MICHIGAN

jeffery a. scott architects p.c.
32316 grand river ave. suite 200
farmington, michigan 48336-3261
(248) 476-8800 fax (248) 476-8833

KROGER ASDs GISDs & GIDs

project no. 23057
sheet no. A5.1.2

copyright © 2024

PLOT FULL SIZE @ 30"x42"