This file was Created on 9/11/2023 @ 11:49:37 AM for D406 by CJ14810.

QUANTITY	NAME	STATUS	ELECTRICAL REQUIREMENTS
1	E38TP	RELO	375W FOR THERMAL PRINTER
1	GE156	RELO	120V 250W ELEC FED FROM RACEWAY FOR EFT PIN PAD & CREDIT CARD READER
1	GE38S	RELO	29W (DEDICATED CKT) FOR POS TERMINAL. WIRED TO KROGER SUB PANEL (NOT STARBUCKS PANEL)
1	GE38	RELO	120V 500W FOR REGISTER (DEDICATED CKT)
2	D23T	RELO	120V 1PH .75AMPS FOR SERVICE SCALE/UPC PRINTER (TOLEDO), PROVIDE A 3/4" COND. TO ECR ROOM
1	DHFSO8SS	RELO	120/208V, 1PH, 56.2A FOR 8' OPEN AIR SERVICE HOT FOOD
2	BR5CS-2	RELO	41W FOR FANS, 102W FOR LIGHTS ON 4'-11" REF. BAKERY CASE (REQ'D. LOCKED ON DEVICE @ PANEL)
1	F5DN12HX	RELO	75W FOR FANS, 255W FOR LIGHTS ON 12' 5-DECK NARROW FLORAL CASE
1	M5DFR8H	RELO	72W FOR FANS, 295W FOR LIGHTS ON 8' FIVE DK FRESH MEAT CASE. MOUNT J.B. 1'-6" AB FL
1	BGDNIC6HI	NEW	130W FOR FANS, 182W FOR A.S. HTRS., 43W FOR LIGHTS, 1400W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 6' NARROW GLASS DOOR ICE CREAM TEMP GROCERY CASE
4	BVGD12HI	NEW	120V, 48W FOR FANS, 68.2W FOR MULLION LIGHTS, FOR 12FT GLASS DOOR BEVERAGE CASE
1	DAWIMTG12HX	NEW	352W FOR FANS & A.S. HTRS, 26W FOR GLASS A.S. HTRS., 4800W (208V 1PH) FOR ELEC DEF (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON 12' WIDE ISLAND DAIRY CASE W/ GLASS (MED TEMP)
2	DAWIMTGEHX	NEW	88W FOR FANS & A.S. HTRS., 16W FOR GLASS A.S. HTRS., 1360W (208V 1PH) FOR ELEC. DEF., (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON ICE CREAM TEMP WIDE ISLAND GROCERY END CASE W/GLASS
2	D299TV-48	RELO	120V, 180W, 1PH, FOR 48" DIGITAL MONITOR FOR DELI MENU BOARD. DATA JACK REQUIRED PER UNIT.
1	DM2THF6AM	RELO	120/208V,1PH REQUIRES MINIMUN 38 AMPS MAXIMUM 50 AMPS FOR 6' TWO TIER MOBILE HOT FOOD
4	D1DSC4HP	NEW	120V, 8.6AMP, 1PH CIRCUIT FOR 4'X4' (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA L5-15 TWIST LOCK PLUG.
2	DGD12HI	NEW	120V, 48W FOR FANS, 68.2W FOR MULLION LIGHTS, FOR 12FT GLASS DOOR DELI CASE
1	DMDLI8HC-2	RELO	ELECTRICAL DATA IS PER SIDE. 72W FOR FANS, 256W FOR LIGHTS ON 8' MDLP DELI ISLAND CASE (UNITIZED)
2	DMDLIEHC-2	RELO	18W FOR FANS, 116W FOR LIGHTS ON MDLP DELI ISLAND END CASE
1	DSBHE	NEW	20W FOR FANS, 90W FOR AMB FANS, 800W A/S HTRS, 177W FOR LIGHTS
1	GM22V-2	RELO	120V, 2AMP,1PH CIRCUIT FOR BATTERY ENDCAP WITH LIGHTED VALANCE
5	E102	RELO	56W FOR THINCLIENT & MONITOR
1	E12C	RELO	960W FOR LASER PRINTER (GENERAL USE)
1	E42-17	RELO	120V, 37W, 1PH FOR 19" LED COMPUTER MONITOR
1	E7MFD	RELO	1200W DEDICATED CIRCUIT FOR COPY PRINT SCAN MFD
2	GE186	NEW	120V 1PH 14AMPS FOR MICROWAVE MOUNT RCPT 4'-0" AB. FL.
1	GE41	NEW	SEE KROGER A&E STANDARDS FOR WHERE PLUGMOLD IS REQUIRED
3	GE96B	RELO	120V 840W FOR BATTERY CHARGER MOUNT OUTLET 2'-0" AB FL FOR ELECTRONIC SHOPPING CART (REAR DRIVE)
1	GGDNIC8PHI	NEW	75W FOR FANS, 419 FOR A.S. HTRS, 240W FOR LIGHTS, 2720W (208V 1PH) FOR ELEC DEF (TO PANEL IN MECH HOUSE FOR DEF WIRING) ON 8' NARROW GLASS DOOR ICE CREAM TEMP GROCERY CASE
2	M1DSC4HP	NEW	120V, 8.6AMP, 1PH CIRCUIT FOR 4'X4' (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA L5-15 TWIST LOCK PLUG.
2	M1DSC4HP	RELO	120V, 8.6AMP, 1PH CIRCUIT FOR 4'X4' (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA L5-15 TWIST LOCK PLUG.
1	M5DFRNG8HI	NEW	120V, 48W FOR FANS, 132.1W FOR HIGH OUTPUT CANOPY LIGHTS AND FOUR ROWS OF SHELF LIGHTS, FOR 8' FIVE-DECK FRESH MEAT CASE (NO GLASS)
2	MGDNLT12HI	NEW	326W FOR FANS, 455W FOR A.S. HTRS, 108W FOR LIGHTS, 3500W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 12' NARROW GLASS DOOR LOW-TEMP GROCERY CASE
4	MWIMTG8HX	NEW	248W FOR FANS & A.S. HTRS., 18W FOR GLASS A.S. HTRS., 3200 (208V 1PH) FOR ELEC. DEF. (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON 8' ICE CREAM TEMP WIDE ISLAND GROCERY CASE W/GLASS
4	MWIMTGEHX	NEW	88W FOR FANS & A.S. HTRS., 16W FOR GLASS A.S. HTRS., 1360W (208V 1PH) FOR ELEC. DEF., (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON ICE CREAM TEMP WIDE ISLAND GROCERY END CASE W/GLASS
1	C55MWK	RELO	120V, 1.25AMP, 1PH CIRCUIT FOR 55" MONITOR WITH WALL MOUNT KIT
2	CR-2	NEW	120V, 15AMP, 1PH CIRCUIT FOR SINGLE RACK CHARGING STATION
1	CGDLT5HSC	NEW	208V, 20AMP, 1PH 4 WIRE, SINGLE POINT ELECTRIC FOR 2 DOOR FREEZER (SELF-CONTAINED)
1	CGDMT12HSC	NEW	208V, 20AMP, 1PH 4 WIRE FOR CONDENSING UNIT, 120V 15AMP, 1PH, FOR CASE POWER FOR 6 DOOR COOLER (SELF-CONTAINED)
1	P1DSC4HP	NEW	120V, 8.6AMP, 1PH CIRCUIT FOR 4'X4' (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA L5-15 TWIST LOCK PLUG.
1	P1DSC4HP	RELO	120V, 8.6AMP, 1PH CIRCUIT FOR 4'X4' (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA L5-15 TWIST LOCK PLUG.
1	P1DSC5SI_CM	RELO	208V, 18.8AMP, 1PH FOR 5'X5' REFRIGERATED PROMO CASE (SELF-CONT) UNIT COMES WITH 10' CORD AND L6-20P NEMA PLUG.
1	PMSC6M-3	RELO	240V,9.5.5AMP, 1PH FOR 6' ULTRA FRESH BERRY CASE (SELF CONTAINED) UNIT COMES WITH 9' CORD AND L14-30P NEMA PLUG.
2	PMSC8M-3	RELO	240V,9.5AMP, 1PH FOR 8' ULTRA FRESH BERRY CASE (SELF CONTAINED) UNIT COMES WITH 9' CORD AND L14-30P NEMA PLUG.
1	S5DFRN8HI	NEW	120V, 48W FOR FANS, 132.10W FOR HIGH OUTPUT CANOPY LIGHTS AND FOUR ROWS OF SHELF LIGHTS, FOR 8' FIVE-DECK SEAFOOD CASE (NO GLASS)
1	SGDNLT12HI	NEW	326W FOR FANS, 455W FOR A.S. HTRS, 108W FOR LIGHTS, 3500W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 12' NARROW GLASS DOOR LOW-TEMP GROCERY CASE
1	T6S	RELO	PROVIDE POWER FOR TABLE TOP EQUIPMENT AS SHOWN ON LEGEND & 800W. CONVENIENCE OUTLETS, 4'-0" AB.FL. AS REQUIRED BY CODE

This file was Created on 9/11/2023 @ 11:49:37 AM for D406 by CJ14810.

QUANTITY	NAME	STATUS	ADDITIONAL REQUIREMENTS
1	GE156	RELO	IF PART OF CHECKSTAND OR AUAS STAND (1 DATA PATCH); OTHERWISE (1 DATA JACK)
1	GE38S	RELO	1 DATA, 1 VOICE JACK REQUIRED
1	GE38	RELO	IF PART OF CHECKSTAND OR AUAS STAND (1 DATA PATCH); OTHERWISE (1 DATA JACK, 1 VOICE JACK)
2	D23T	RELO	1 DATA JACK
3	GE64D	NEW	SEE ASD-152
1	DAWIMTG12HX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V 3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
2	DAWIMTGEHX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V 3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
2	D299TV-48	RELO	1 DATA JACK
5	E102	RELO	1 DATA JACK
1	E7MFD	RELO	1 DATA, 1 VOICE JACK
4	MWIMTG8HX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V 3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
4	MWIMTGEHX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V 3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT

issued for: BIDS AND PERMITS 04/15/2024
90% OWNER REVIEW 03/07/2024

PROPOSED MINOR INTERIOR REMODEL FOR:

STORE NO. D-406
1200 E BRISTOL RD
BURTON, MI 48529

THE KROGER CO. OF MICHIGAN

jeffery a. scott architects p.c.
32316 grand river ave. suite 200
farmington, michigan 48336-3261
(248) 476-8800 fax (248) 476-8833

EQUIPMENT SCHEDULE

project no. 23057

sheet no. E6.1

PLOT FULL SIZE ● 30"x42"

copyright © 2024