

1. SEE ROOM FINISH SCHEDULE A6.1, DECOR DRAWINGS AND SPECIFICATIONS FOR FINISHES AND ADDITIONAL INFORMATION.


15. FOR NEW FRAMED WALLS INDICATED TO EXTEND EXISTING PREP ROOM WALLS, INSTALL FOIL FACE OF INSULATION TOWARD THE WARM SIDE, FOR EXAMPLE, THE BACK ROOM OR SALES SIDE RATHER THAN INSIDE PREP ROOM.

(ALL ACCESSORIES SHALL BE ICC ANSI A117.1-2009 COMPLIANT)

KROGER SUPPLIED & CONTRACTOR INSTALLED EQUIPMENT:

TA-1 SOAP DISPENSER.

TA-3 PAPER TOWEL MANUAL
"TENSION" DISPENSER.



BARRIER FREE SHALL COM
WITH ICC ANSI A117.1-2009

SCALE: NONE




NO SCALE

1. THE EXISTING ROOF IS TO REMAIN. PORTIONS OF THE ROOF TO BE PATCHED & REPAIRED OR REWORKED AS REQUIRED DUE TO ANY DEMOLITION, REMOVAL OF EXISTING ITEMS, ANY NEW CONSTRUCTION, AND INSTALLATION OF NEW ITEMS. MATCH EXISTING ROOFING MATERIAL (IE. MEMBRANE, INSULATION, STEEL DECKING) AND PROVIDE NEW MATERIAL AS REQUIRED TO PATCH / REPAIR ROOF AND MATCH EXISTING SLOPE.

- AND
TING ROOFING
EL DECKING)
TO PATCH /




NO SCALE




SCALE: NONE

NOTES:

1. SEE SHEET A1.2 FOR CONCRETE
REMOVAL AND REPLACEMENT PLAN



NO SCALE



NO SCALE