

--- VINYL WALL BASE (WB-701). SEE ASD-51D, SHEET A5.1.1.  
(TYPICAL AT AREAS WITH NEW FLOOR FINISHES AND  
AREAS WITH NEW WAINSCOT, SEE I1.4)


----- STAINLESS STEEL CASE FLASHING TYPICAL ON THE  
BACK OF PREP AREA CASES. SEE GISS-14 ON A5.1.2.

--- QUARRY TILE COVE BASE. SEE SPECIFICATIONS  
SEE ASD-51C, SHEET A5.1.1.

**NOTE:**  
REPLACE ANY MISSING / DAMAGED COVE BASE IN THE PREP  
AREAS THAT ARE NOT RECEIVING NEW BASE. TO MATCH  
EXISTING QUARRY TILE FLOORING COVE BASE. SEE ASD-51C  
ON A5.1.1 FOR COVE BASE. SEE SPECIFICATIONS. (TYP)

DECOR SERIES #600 (BOUNTIFUL DECOR - P & P) #700 (ARTISAN DECOR)

PURCHASED / INSTALLED BY G.C.



 <p>VT-X1</p> <p>MATCH EXISTING VCT</p>	 <p>VT-X2</p> <p>MATCH EXISTING LVT</p>	<p>REPLACE EXISTING LVT WITH SALVAGED LVT FROM USCAN AREA.</p>
--	--	--

- A. ALL FLOOR FINISHES TILES TO BE PER SPECIFICATIONS UNLESS NOTED OTHERWISE. IF CUTTING TILE IS NECESSARY, NO TILE SHALL BE LESS THAN 4" EXCEPT AT WALLS.
- B. WHERE THE THICKNESS OF TWO FLOOR FINISHES ADJOIN - PROVIDE TRANSITION AS REQUIRED TO PRODUCE FLUSH JOINT.
- C. ALL NEWLY EXPOSED WALLS TO RECEIVE NEW WALL BASE PER SPECIFICATIONS UNLESS NOTED OTHERWISE. REPAIR / REPLACE ANY MISSING OR DAMAGED WALL BASE (BOTH IN SALES AND PREP AREAS) TO MATCH EXISTING.
- D. VERIFY ALL FLOOR FINISHES AT PREP AREAS W/LOCAL HEALTH DEPARTMENT BEFORE PROCEEDING.
- E. VERIFY ALL FLOOR FINISH ALIGNMENTS PER PLAN WITH FIXTURE LOCATIONS AND DIMENSIONS PRIOR TO STARTING WORK.
- F. WRITTEN DIMENSIONS HAVE PRECEDENCE OVER SCALE.
- G. G.C. TO CONTACT ARCHITECT AND/OR KROGER PROJECT MANAGER WITH ANY DISCREPANCIES BETWEEN JOB SITE CONDITIONS AND DRAWINGS BEFORE PROCEEDING.
- H. SALES FLOOR FINISH TO CARRY UNDERNEATH SHELVING, FIXTURES AND NEW FLOORING. REFRIGERATED CASES, EXISTING REFRIGERATED CASES AND ISLANDS REMAINING IN PLACE WILL REQUIRE THE FLOOR FINISH TO CONTINUE BEYOND THE CASES KICK PLATE. EXTENTS OF NEW FLOOR FINISH AS INDICATED ON PLAN.
- I. SEE MANUFACTURER'S SPECIFICATIONS FOR INSTALLATION REQUIREMENTS OF FINISHES SPECIFIED IN THESE DRAWINGS.
- J. PROVIDE PROPER AND REQUIRED VENTILATION FOR INSTALLATION OF ALL RESINOUS FLOORING.
- K. THE CONTRACTOR WILL NEED TO WALK THE STORE PRIOR TO BIDDING TO VERIFY ANY DAMAGED OR PROBLEMATIC AREAS THAT NEED TO BE REPAIRED DURING CONSTRUCTION. THE CONTRACTOR IS RESPONSIBLE FOR THE FLOOR FINISH PRIOR TO POLISHING CONCRETE OR INSTALLING NEW FLOOR FINISHES.

1. FIELD CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS PRIOR TO STARTING WORK.
2. CONTACT KROGER PROJECT MANAGER (PRIOR TO PLACEMENT OF ANY FLOOR FINISHES) TO VERIFY COORDINATION W/ FINAL FLOOR FINISH PLAN AND LATEST MARKETING AREA FIXTURE PLAN.
3. PAINT OR RE-PAINT FIRE EXIT LANES AT BACKROOM AREAS. (TYPICAL LANES ARE A LIMITED BORDER STRIPE EACH SIDE OF LANE. BORDER STRIPE TO BE 3" WIDE AND SPACED 44" APART AT THE OUTSIDE DIMENSIONS.)
4. SAW CUT AREAS, TRENCHES AND PITS REQUIRE NEW FLOOR FINISH AFTER ALL WORK HAS BEEN INSTALLED AND TESTED AND CONCRETE HAS CURED.
5. PATCH AND REPAIR ALL EXISTING TRANSITION STRIPS & THRESHOLDS AND ADJACENT FLOORING TO REMAIN AS REQUIRED.
6. G.C. TO PROVIDE ALL NECESSARY FLOOR PREP PRIOR TO INSTALLING NEW FLOOR FINISHES. THIS INCLUDES ANY REQUIRED CONCRETE PREP AND THE ADJUSTING OF ALL FLOOR DRAINS, CLEANOUTS, ACCESS PLATES, HOSE BIBS, ELECTRICAL OUTLETS, & OTHER FLOOR MOUNTED ITEMS DUE TO NEW FLOOR FINISH.
7. FOR VINYL WALL BASE, SEE ASD-51D ON SHEET A5.11 AND KROGER SPECIFICATIONS. REPLACE WALL BASE FOR AREAS WITH NEW FLOOR OR WALL FINISHES. PROVIDE NEW WALL BASE AT NEW WALLS.
8. PAINT #8 STRIPE ON FLOOR AGAINST WALL [EXCEPT ON COOLER AREAS] WITH NEW WALL FINISHES. BE SURE STRIPE IN THE STAGING AREA AND DOCK. SEE KROGER SPECIFICATIONS.
9. STAINLESS STEEL CASE FLASHING. INSTALL ON THE BACK SIDE OF NEW & RELOCATED FRONT LINE PREP CAGES. INSTALL ON EXISTING CAGES THAT DO NOT HAVE CASE FLASHING. SEE GISO-14 ON A5.12.
10. PATCH / REPAIR AND CLEAN EXISTING FLOORING AS REQUIRED AT NEW OPENING INTO PREP AREA.
11. REPLACE ALL DAMAGED OR SOILED VCT / LVT ON SALES FLOOR AND FLOORING THAT HAS BEEN EXPOSED FROM UNDER A DEMOLISHED OR RELOCATED FIXTURE. REPLACE FLOORING TO MATCH EXISTING COLOR AND PATTERN ON SALES FLOOR. SALVAGE DEMOLVED LVT TO REUSE TO PATCH AREAS OF THE EXISTING LVT FLOORING.

**DECOR SERIES EXISTING #600  
(BOUNTIFUL DECOR - PAINT AND PUTTY)**

THE EXISTING DECOR IS TO REMAIN. ALL NEW WORK TO MATCH THE EXISTING DECOR AND FINISHES, U.O.N.

SEE THE JSA CONSTRUCTION DRAWINGS AND PROJECT SPECIFICATIONS.  
SEE PROJECT SPECIFICATION'S SECTION 01 61 27 "DECOR INTERIOR  
FINISHES AND COLORS - BOUNTIFUL" FOR INFORMATION ON THE  
EXISTING FINISHES. SEE PROJECT SPECIFICATION'S SECTION 01 61 27  
"DECOR INTERIOR FINISHES AND COLORS - ARTISAN" FOR INFORMATION  
ON NEW FINISHES IN INDICATED AREAS.

REFER TO THE PAINT & PUTTY STANDARDS FOR BOUNTIFUL DECOR UPDATE, "DECOR DEMO / PAINT & FINISHES / STENCILS" GUIDE. THIS DECOR GUIDE WILL SUPERSEDE THE FINISHES AND COLORS LISTED IN DECOR SPECIFICATIONS.

COORDINATE EXTENT OF FINISH AND DECOR WORK WITH THE KROGER PROJECT MANAGER.

issued for:	<b>BIDS AND PERMITS</b>	<b>04/15/202</b>
	<b>90% OWNER REVIEW</b>	<b>03/07/202</b>


**PROPOSED MINOR INTERIOR  
REMODEL FOR:**



STORE NO. D-406

1200 E BRISTOL RD  
BURTON, MI 48529

**THE KROGER CO. OF MICHIGAN**



jeffery a.  
scott  
architects p.c.

32316 grand river ave. suite 200  
farmington, michigan 48336-3261  
(248) 476-8800 fax (248) 476-8833

## FLOOR FINISH PLAN


project no.	
-------------	--

23057

sheet no

## A1.6

- SEE FINISH PLAN ON I1.4 AND FINISH SCHEDULE ON A6.1 FOR WALL FINISHES.
- SEE CONCRETE REMOVAL AND PLACEMENT PLAN ON A1.2 FOR EXTENTS OF CONCRETE WORK.



SCALE: 3/32" = 1'-0"

