



2 PLAN CONCRETE PLACEMENT / FLOOR FINISH
SCALE 3/32" = 1'-0"

1 PLAN CONCRETE PLACEMENT / FLOOR FINISH
SCALE 3/32" = 1'-0"

General Notes

1. REFER TO ASD-4B, ASD-4-C AND ASD-4D FOR FLOOR FINISH TRANSITION. REFER TO ASD-51E FOR TO WALL TO FLOOR BASE TYPE-E DETAIL.
2. WHEN SAWCUTTING THE CONCRETE FLOOR FOR TRENCHES/PTS THERE IS TO BE NO OVERCUTS.
3. ALL TRENCHING TO BE 1'-4" WIDE UNLESS NOTED OTHERWISE. REFER TO PLUMBING AND REFRIGERATION DRAWINGS FOR FINAL LOCATION.
4. G.C. TO INCLUDE IN THEIR BID THE REMOVAL AND REPLACEMENT OF 2600 SF DAMAGED FLOOR T.I.E.
5. G.C. TO REFER TO DIVISION 9 OF SPECS FOR FINISHES.
6. ALL TRENCHING IS SHOWN AS REFERENCE. REFER TO PLUMBING DRAWINGS FOR UNDERGROUND PLUMBING.

Coded Notes

- 03A GRAY CONCRETE WITH SMOOTH FINISH WHEN PLACING NEW CONCRETE, DOWEL INTO ADJACENT SLAB WITH #4 BARS AT 24" OC WITH A MINIMUM EMBEDMENT OF 8". REPLACEMENT FINISHES TO MATCH ADJACENT EXISTING FLOOR FINISH. SEE ASD-49
- 09A NEW 5'-0" X 4'-0" PAINTED SQUARE. FINAL LOCATION TO BE DETERMINED BY KROGER ENGINEER
- 09B REPAIR ALL BACK OF HOUSE FLOOR STRIPING AND CAUTION LINES AROUND DOCK LEVELER.
- 09C INSTALL NEW RUBBER TREADS ON EXISTING STAIRS.
- 09D REPAIR 50 SF OF DAMAGED GROUT

Shading Legend

- EXISTING TO REMAIN
- LIMITS OF CONCRETE TRENCHING SLAB REPLACEMENT
- LIMITS TO INSTALL NEW VCT
- LIMITS TO INSTALL NEW CARPET
- LIMITS OF FLOOR TO BE DEEP CLEAN FLOORBASE AND INSTALL ADSL TREATMENT (DEEP CLEAN AND INSTALL ADSL TREATMENT 4' OF A.F.F. ON TILE WALLS IN RESTROOMS)
- LIMITS OF FLOOR AND BASE TO BE DEEP-CLEANED ONLY

#	Date	Change Description

KROGER N641
PORT CLINTON
2028 EAST HARBOR ROAD
PORT CLINTON, OHIO 43402
for
THE KROGER COMPANY

Moody Nolan
300 Spruce Street Suite 300 Columbus, Ohio 43215
Phone: (614) 461-4664 Fax: (614) 290-8861
www.moodynolan.com

Dwg. Coord.: JWB	Tech. Coord.:	Proj #: 23016.01
PLAN CONC. PLC./FLOOR FINISH	A1.2	
BID/PERMIT		2/2/2024