

QUANTITY	NAME	STATUS	ELECTRICAL REQUIREMENTS
2	E385S	RELO	17W FOR SCANNER/SCALE
3	E38TP	RELO	375W FOR THERMAL PRINTER
2	E38TS	RELO	18W FOR TOUCHSCREEN POS (FOR OEM MOUNT)
3	G6156	RELO	120V 250W ELEC DEF FROM RACEWAY FOR LEFT PIN PAD & CREDIT CARD READER
1	G6135	RELO	20W (DEDICATED CKT) FOR POS TERMINAL - WIRE TO KROGER SUB PANEL (NOT STARBUCKS PANEL)
3	G638	RELO	120V 500W FOR REGISTER (DEDICATED CKT)
2	ALS966S-F5	RELO	500W FOR REGISTER (DEDICATED CIRCUIT) AND 264W FOR BELT ON ENTERPRISE STANDARD CHECKSTAND (96" FM, 65" RM)
1	DJ23T	RELO	120V 1PH .75AMPS FOR SERVICE SCALE/UPC PRINTER (TOLEDO), PROVIDE A 3/4" COND. TO ECR ROOM
1	F47WL_SR	NEW	(2)120V, 20A DUPLEX OUTLETS & 112W FOR LIGHTS ON FLORAL WORKSTATION
1	S24T	RELO	120V 1PH .75AMPS FOR SERVICE SCALE/UPC PRINTER (TOLEDO), PROVIDE A 3/4" CONDUIT TO ECR ROOM
1	DASD6HP	RELO	35W FOR FANS, 35.8W FOR LIGHTS ON 6' FIVE-DECK DAIRY CASE MOUNT J.B. 1'-6" AB FL
2	DASDUL12HP	RELO	130W FOR FANS, 64.5W FOR LIGHTS, ON 12' 5-DECK DAIRY CASE W/ ULTRA LOW FRONT RAIL, MOUNT J.B. 1'-6" AB FL
1	DASDUL8HP	RELO	87W FOR FANS, 43W FOR LIGHTS, ON 6' 5-DECK DAIRY CASE W/ ULTRA LOW FRONT RAIL, MOUNT J.B. 1'-6" AB FL
2	DAMDLGX12HP	RELO	42W FOR FANS, 64.5W FOR LIGHTS ON 12' MDLP DAIRY CASE (60" H)
2	DAMDLGX6HP	RELO	28W FOR FANS, 29.8W FOR LIGHTS ON 6' MDLP DAIRY CASE (60" H)
1	CHM0L-12	NEW	120V, .72 AMPS, 1PH FOR FANS & LED LIGHTS FOR MURRAY'S 12 PAN OLIVE BAR INLINE CASE
7	CU4-60	NEW	120 VOLT POWER DROP REQUIRED PER 24" RUN DOUBLE SIDED GONDOLA (72 WATT MAX PER 3' OR 4' SECTION) RUN NOT TO EXCEED 24" PER POWER DROP. REFERENCE VENDORS INSTALATION MANUAL FOR DETAILS.
1	CU4L-60	NEW	120 VOLT POWER DROP REQUIRED PER 24" RUN DOUBLE SIDED GONDOLA (72 WATT MAX PER 3' OR 4' SECTION) RUN NOT TO EXCEED 24" PER POWER DROP. REFERENCE VENDORS INSTALATION MANUAL FOR DETAILS.
1	CU4R-60	NEW	120 VOLT POWER DROP REQUIRED PER 24" RUN DOUBLE SIDED GONDOLA (72 WATT MAX PER 3' OR 4' SECTION) RUN NOT TO EXCEED 24" PER POWER DROP. REFERENCE VENDORS INSTALATION MANUAL FOR DETAILS.
2	DAWIMTGEHX	NEW	88W FOR FANS & A.S. HTRS., 16W FOR GLASS A.S. HTRS., 1360W (208V 1PH) FOR ELEC. DEF., (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON ICE CREAM TEMP WIDE ISLAND GROCERY END CASE W/GLASS
2	D299TV-48	RELO	120V, 180W, 1PH, FOR 48" DIGITAL MONITOR FOR DELI MENU BOARD. DATA JACK REQUIRED PER UNIT.
2	D77B	RELO	120V, 1550W, 1PH FOR RICE COOKER
1	DCBS08AT	RELO	208V, 1PH, 1935W FOR HEAT LAMP, 208V, 1PH, 224W FOR DROP-IN WARMER, 208V, 1PH, 1514W FOR DROP-IN WARMER, 208V, 1PH, 780W FOR HEATED DRAWERS
1	DM2THF6AM	RELO	120V/208V, 1PH REQUIRES MINIMUM 30 AMPS FOR 6' TWO TIER MOBILE HOT FOOD
1	DM2SC4HP	NEW	120V, 8.6AMP, 1PH CIRCUIT FOR 4X4" (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA 5-15P PLUG.
1	DCFM6DHC	NEW	120V, 16W FOR FANS, 39W FOR LED LIGHTS FOR 6' MDLP SELF SERVICE IN LINE COLD FOOD CASE
1	DCFM8DHC	NEW	120V, 16W FOR FANS, 54W FOR LED LIGHTS FOR 8' MDLP SELF SERVICE IN LINE COLD FOOD CASE
1	DMDLR8HC	NEW	120V, 32W, FOR FANS, 41W FOR LED LIGHTS, FOR 8' FRESH SLICED MULTI DECK CASE (REMOTE)
1	DMDLR8HC	NEW	120V, 32W, FOR FANS, 41W FOR LED LIGHTS, FOR 8' FRESH SLICED MULTI DECK CASE (REMOTE)
1	DFPSSUS8B-2	RELO	300W FOR FANS, 166W FOR LIGHTS, 51W FOR ANTI-SWEAT HEATERS FOR 8' SUSHI PREP/DISPLAY CASE W/ REF. REAR STORAGE
1	GM22V-2	NEW	120V, 2AMP, 1PH CIRCUIT FOR BATTERY ENDCAP WITH LIGHTED VALANCE
1	GM7M-35	NEW	120V, 79.2W, FOR 3 FT KPNR/OTC LIGHT VALANCE (STARTER)
4	GM7M-45	NEW	120V, 82.3W, FOR 4 FT KPNR/OTC LIGHT VALANCE (STARTER)
39	GM7M-4	NEW	120V, 82.3W, FOR 4 FT KPNR/OTC LIGHT VALANCE
1	E102	RELO	56W FOR THINCLINT & MONITOR
1	E12C	RELO	960W FOR LASER PRINTER (GENERAL USE)
2	G6186	NEW	120V 1PH 14AMPS FOR MICROWAVE MOUNT RCPT 4'-0" AB FL.
4	HRD2	NEW	120V, 8.33AMP, 1PH FOR DYSON LOW VOLTAGE HAND DRYER
2	G85BSC-1	NEW	120V, 2 AMP, 1PH FOR 24" CHECKSTAND REFRIGERATED MERCHANDISER, COMES WITH 9' CORD WITH NEMA 5-15P PLUG.
5	G85BSC-2	NEW	120V, 2 AMP, 1PH FOR CHECKSTAND REFRIGERATED MERCHANDISER, COMES WITH 10' CORD WITH NEMA 5-15P PLUG.
1	GDGNC10H	NEW	260W FOR FANS, 364W FOR A.S. HTRS, 86W FOR LIGHTS, 2800W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 10' NARROW GLASS DOOR ICE CREAM TEMP GROCERY CASE
6	GDGNC12H	NEW	326W FOR FANS, 455W FOR A.S. HTRS, 108W FOR LIGHTS, 3500W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 12' NARROW GLASS DOOR ICE CREAM TEMP GROCERY CASE
1	GDGNC16PH	NEW	130W FOR FANS, 182W FOR A.S. HTRS., 45W FOR LIGHTS, 1400W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 6' NARROW GLASS DOOR ICE CREAM TEMP GROCERY CASE
1	GDGNC12H1H	NEW	120W FOR FANS, 180W FOR A.S. HTRS, 86W FOR LIGHTS, 2800W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 10' NARROW GLASS DOOR LOW-TEMP GROCERY CASE
12	GDGNC12H3	NEW	336W FOR FANS, 455W FOR A.S. HTRS, 108W FOR LIGHTS, 3500W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 12' NARROW GLASS DOOR LOW-TEMP GROCERY CASE
3	GDGNC18H	NEW	195W FOR FANS, 273W FOR A.S. HTRS., 65W FOR LIGHTS, 2100W (208V 1PH) FOR ELEC DEF. (TO PANEL FOR DEF WIRING) ON 8' NARROW GLASS DOOR LOW-TEMP GROCERY CASE
2	MDSDC4HP	NEW	120V, 8.6AMP, 1PH CIRCUIT FOR 4X4" (SELF-CONT) REF. MOBILE MERCHANDISER SUPPLIED WITH CORD & NEMA 5-15P PLUG.
1	MDSDUL12HX	NEW	352W FOR FANS & A.S. HTRS, 26W FOR GLASS A.S. HTRS., 4800W (208V 1PH) FOR ELEC DEF (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON 12' WIDE ISLAND DAIRY CASE W/ GLASS (MED TEMP)
2	MDWIDT8GHX	NEW	248W FOR FANS & A.S. HTRS., 18W FOR GLASS A.S. HTRS., 3200 (208V 1PH) FOR ELEC. DEF. (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON 8' ICE CREAM TEMP WIDE ISLAND GROCERY CASE W/GLASS
2	MDWIDTGEHX	NEW	88W FOR FANS & A.S. HTRS., 16W FOR GLASS A.S. HTRS., 1360W (208V 1PH) FOR ELEC. DEF. (ROUTE CONDUIT TO MECH CENTER OR PROTOCOL UNIT FOR CONTROL CKT & DEFROST WIRING) ON ICE CREAM TEMP WIDE ISLAND GROCERY END CASE W/GLASS
1	MDWIDTGEHX	NEW	88W FOR FANS & A.S. HTRS., 16W FOR GLASS A.S. HTRS., 1360W (208V 1PH) FOR ELEC. DEF., (ROUTE CONDUIT TO MECH CENTER OR

QUANTITY	NAME	STATUS	ADDITIONAL REQUIREMENTS
3	GE156	RELO	IF PART OF C-CHECKSTAND OR ALIAS STAND (1 DATA PATCH); OTHERWISE (1 DATA JACK)
1	GE38S	RELO	1 DATA, 1 VOICE JACK REQUIRED
3	GE38	RELO	IF PART OF C-CHECKSTAND OR ALIAS STAND (1 DATA PATCH); OTHERWISE (1 DATA JACK, 1 VOICE JACK)
2	ALS966S-FS	RELO	3 DATA, 1 VOICE JACK
1	DZ3T	RELO	1 DATA JACK
1	S24T	RELO	1 DATA JACK
3	GE54D	NEW	SEE ASD-152
2	DANIMTGEHX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V/3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
2	DZ99TV48	RELO	1 DATA JACK
1	E102	RELO	1 DATA JACK
1	MMWDTG12HX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V/3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
2	MMWDTG9HX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V/3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
1	MMWDTG8HX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V/3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT
1	MMWDTG7HX	NEW	LOADS SHOWN FOR ELECTRIC DEFROST ARE 208V/3PH (UNLESS NOTED OTHERWISE) AND LOADS USED ONLY FOR SIZING CONDUIT

23044	E6.1
-------	------

copyright © 2024