

1. EXISTING COLUMN WRAPS TO REMAIN. REPLACE ANY DAMAGED COLUMN WRAPS AND RESEAL EDGES. COLUMN WRAP TO BE TO 5'-0" AFF [OR TO MATCH HEIGHT OF EXISTING COLUMN WRAP] PER DETAIL ASD-63, SHEET A5.11. SEE PROJECT SPECIFICATIONS SECTION 01 61-13. PAINT COLUMNS ABOVE COLUMN WRAP AND ALL COLUMNS THAT FALL WITHIN SHELVING OR CASES PER THE DECOR SPECIFICATIONS & DECOR DRAWINGS. SEE R1SD-50, SHEET A5.12. FOR COLUMNS THAT FALL WITHIN SHELVING. COLUMNS WITH-IN PREP AREAS TO BE STAINLESS STEEL FROM FLOOR TO CEILING. SEE ASD-63, A5.11.
2. PARTITIONS TO BOTTOM OF DECK OR JOIST AND PARTITIONS WITH RECESSED EQUIPMENT [ELECTRIC PANELS, FLY GRIDS, ETC.] OR PLUMBING FIXTURES SHALL BE 6" METAL STUDS.
3. PROVIDE WOOD BLOCKING [INSERTED IN METAL STUDS] IN PARTITION THIS AREA, FOR SHELVING BRACKET SUPPORT [6'-0" TO 8'-0"], FOR BABY CHANGING STATION [FROM FLOOR TO EXHAUST HOOD/STAINLESS STEEL FROM 8'-0" TO 8'-0"] FOR WALL MOUNTED FIRE EXTINGUISHERS AND/OR FOR MISCELLANEOUS FIXTURES AND SHELVING AS REQUIRED. SEE SPECIFICATIONS SECTION 06 10 53 FOR ADDITIONAL BLOCKING INFORMATION. PATCH/REPAIR WALL & FINISHES AS REQUIRED WHEN ADDING BLOCKING TO EXISTING WALLS.
4. REMOVABLE PROTECTIVE POST[S] (SALES AREA), SEE SPECS. POST[S] TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET. SEE ASD-19 ON SHEET A5.11.
5. REFRIGERATED CASE CORNER GUARD (SALES AREA), SEE SPECS. GUARD[S] TO BE SUPPLIED & INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET. SEE ASD-160 (ASD-160A FOR GLASS DOOR CASES) ON SHEET A5.12.
6. PROVIDE B.S. CORNER GUARD. SEE ASD-65A, SHEET A5.11. REPLACE ANY MISSING OR DAMAGED CORNER GUARDS.
7. PROVIDE NEW SUBSTRATE AND CEMENT TO RECEIVE NEW FINISHES AS REQUIRED FOR NEW WALL OR DUE TO REMOVAL OF EXISTING FINISHES SURS. TO BE PREPARED JOINTS, JOINTS, AFF & MOISTURE RESISTANT GYPSUM BOARD TO CEILING AT PREP AREAS AND RESTROOMS (AT NEW WALL TILE & FRP). PROVIDE GYPSUM BOARD AT ALL OTHER AREAS AS REQUIRED. PROVIDE A CLEAN FLUSH SURFACE TO APPLY NEW WALL FINISH AS INDICATED.
8. INCLUDE ALL REQUIRED TRADES, LABOR AND MATERIALS TO TEMPORARILY MOVE ALL EQUIPMENT, FIXTURES, & ACCESSORIES FOR INSTALLATION OF NEW FLOOR AND/OR WALL FINISHES AS INDICATED ON SHEETS A.6 & 11.4.
9. MODIFY WALL, PATCH & REPAIR AS REQUIRED FOR REFRIGERATION LINE WORK. COORDINATE LOCATIONS WITH REFRIGERATION TRADE. SEE DETAIL 521, SHEET A5.2.
10. ALL NEW REFRIGERATION, PLUMBING, AND ELECTRICAL CONDUIT DROPS ON THE SALES FLOOR ARE TO BE TIGHTLY GROUPED TOGETHER, SECURED SIMILAR TO R1SD-34B AND R1SD-35 ON SHEET R5.1, AND PAINTED TO MATCH COLUMNS..
11. ALL NEW REFRIGERATION AND ELECTRICAL CONDUIT CHASES AT ISLAND CASES AND FRONT LINE SERVICE CASES ARE TO BE ENCLOSED IN PVC TUBING AND PAINTED TO MATCH COLUMNS. SEE REFRIGERATION LAYOUT ON SHEET R11 AND DETAILS R1SD-36 AND R1SD-36A ON SHEET R5.1. FOR CHASES THAT EXTEND TO THE FLOOR, COVER WITH STAINLESS STEEL COLUMN WRAP FROM FLOOR TO 5'-0" AFF [TO MATCH HEIGHT OF EXISTING COLUMN WRAP]. SIMILAR TO ASD-63 ON SHEET A5.11.
12. NEW KITCHENETTE MILLWORK (CABINETS, COUNTER, SINK, TA-1 & TA-3). PLAN NOTE 3. SEE PLUMBING SHEETS.
13. MOUNTING HEIGHT FOR MISCELLANEOUS TOILET ROOM FIXTURES SHALL NOT EXCEED 3'-4" ABOVE FLOOR.
14. NEW OR RELOCATED DIGITAL MONITOR MENU BOARDS [2]. HANG/MOUNT BELOW SOFFIT. SEE ASD-72 ON A5.12 FOR MOUNTING DETAILS. GC TO INSTALL MONITOR AND PROVIDE / INSTALL ALL REQUIRED HARDWARE (UNISTRUT, THREADED ROD, AND MOUNTING BRACKET). VERIFY ANGLE OF MONITOR FOR BEST VIEW OF THE DISPLAY. ALL LOW-VOLTAGE WORK TO BE PROVIDED BY THE GC. VERIFY LOCATION WITH KROGER PM.



(ALL ACCESSORIES SHALL BE ICC ANSI
A117.1-2009 COMPLIANT)

TA-1	SOAP DISPENSER. SEE PSD-50.
TA-2	TRASH RECEPTACLE
TA-3	PAPER TOWEL MANUAL "TENSION" DISPENSER.
TA-4	NOT USED
TA-5	NOT USED
TA-6	RECESSED SANITARY NAPKINS DISPENSER, 11 3/4" WIDE X 6 1/2" DEEP X 26 1/8" HIGH. OPTIONALLY INSTALLED PER DIVISION.
TA-7	JUMBO, JR. BATHROOM TISSUE DISPENSER (SMOKE GRAY), 10.610" WIDE X 5.390" DEEP X 11.290" HIGH.
TA-8	GRAB BARS, SUPPLIED WITH TOILET PARTITIONS.
TA-9	DIAPER CHANGING STATION, 33.5" WIDE X 3.94" DEEP X 24.75" HIGH
TA-10	PARTITIONS, TOILET/URINAL (TC-701)
TA-11	COAT HOOKS ON INTERIOR OF EACH STALL DOOR, PLUS ADDITIONAL HOOKS PER LOCATIONS INDICATED ON PLANS. SUPPLIED WITH 1/2" PARTITIONS. INSTALL HOOK 4'-0" ABOVE FLOOR, UNLESS NOTE OTHERWISE.
TA-12	SANITARY NAPKINS DISPOSAL RECEPTACLE, 7 1/2" WIDE X 3 7/8" DEEP X 10" HIGH.
TA-13	HOOK & CATCH DOOR HOLDER, PART OF DOOR HARDWARE PACKAGE.
TA-14	WALL MOUNTED CHAIR PROTECTION SEAT.

TA-15 SOLID SURFACE COUNTER TOP,
STAINLESS STEEL SINK BOWLS,
FAUCETS, ETC. CONTRACTOR SHALL
DETERMINE TOP LENGTH PER FIELD
CONDITIONS. TRASH CHUTE TRIM RING,
6" DIAMETER X 2" DEEP. SEE PSD-50
FOR COMPLETE INFORMATION.

TA-16 MIRROR OVER SINK, SPRING LOADED
MIRROR CLIPS AT TOP AND BOTTOM
TO BE DETERMINED BY FIELD. TILES
HAVE BEEN INSTALLED TO WALL. ADA
ACCESSIBLE DECAL ON MIRROR AT EACH
END. COMPLIANT SINK LOCATION. SEE
PSD-50

TA-17 ICC ANSI A17.1 COMPLIANCE RESTROOM
SIGNS MOUNTED ON EACH SIDE OF
DOOR 5'-0" FROM FLOOR TO
CENTERLINE OF SIGN.

TA-18 PLUMBING FIXTURES -- TOILETS,
URINALS, DRINKING FOUNTAINS, WALL
MOUNTED SINKS.

TA-19 36" WIDE X 72" HIGH WALL MIRROR.
MIRRORS TO BE INSTALLED AFTER
TILES HAVE BEEN APPLIED TO WALL.

TA-20 ELECTRIC HAND DRYER DYSON
AIRBLADE V. REFER TO SECTION 10
28.19 TOILET ACCESSORIES IN
SPECIFICATIONS

TA-21 TRASH RECEPTACLE (WALL MOUNTED), 16
1/2" WIDE X 18 1/2" DEEP X 23" HIGH.

(SEE PROJECT SPECIFICATIONS, PLUMBING
DRAWINGS, & DRAWING REF-4 & REF-4A -
RESTROOMS STANDARDS WITH ELEVATIONS (BY
KROGER) FOR ADDITIONAL INFORMATION)

- SEE GENERAL NOTES ON SHEET A1.1
- SEE SHEET I1.4 FOR FINISHES, DECOR, MILLWORK, & FIXTURE / CASE NOTES.

EXISTING WALL EXISTING SOFFIT

NEW WALL NEW SOFFIT

issued for:	BIDS AND PERMITS	02/27/2022
	90% OWNER REVIEW	01/11/2022



THE KROGER CO. OF MICHIGAN



jeffery a.
scott
architects p.c.

32316 grand river ave. suite 200
farmington, michigan 48336-3261
(248) 476-8800 fax (248) 476-8833

ENLARGED PLANS, DETAILS, NOTES

project no

sheet no

23044

A4.1