

1. SEE ROOM FINISH SCHEDULE A6.1, DECOR DRAWINGS AND SPECIFICATIONS FOR FINISHES AND ADDITIONAL INFORMATION.

15. FOR NEW FRAMED WALLS INDICATED TO EXTEND EXISTING PREP ROOM WALLS, INSTALL FOIL FACE OF INSULATION TOWARD THE WARM SIDE, FOR EXAMPLE, THE BACK ROOM OR SALES SIDE RATHER THAN INSIDE PREP ROOM.



SCALE: NONE

ALSO SEE ASD-69,
SHEET A5.1.1

1. SEE SHEET A1.2 FOR CONCRETE
REMOVAL AND REPLACEMENT PLAN.

A. REPLACE EXISTING DAMAGED OR SMOOTH STEEL PLATES / COVERS WITH NEW STAINLESS STEEL PLATES (PLATES OVER 1/2 SQ. FT. IT IS "DIAMOND-PLATED").

B. PLATES ARE TO BE FLUSH WITH FINISH FLOOR.

C. WHERE PLATES ARE LONGER THAN ACCESS OR JUST HIDING OR PATCHING DAMAGED CONCRETE ON THE FLOOR, REMOVE PLATE & CUT/PATCH CONCRETE AS REQUIRED FOR SMOOTH, FLUSH FINISH.

D. GENERAL CONTRACTOR TO VERIFY LOCATIONS & SIZES OF ALL PLATES.

E. GENERAL CONTRACTOR TO PROVIDE UNIT COST PER SQUARE FOOT OF STEEL PLATES. PROVIDE UNIT COST IN THE TRADE PROPOSAL FORM (SECTION OF 42 IS TRADE PROPOSAL) UNDER ITEM 5.

F. RAISE FLOOR COVER AND REMOVE EXISTING DAMAGED ACCESS PORTS (TYP. AT REGISTERS & B-LINES) WITH DIAMOND PLATE COVERS, PROVIDED & INSTALLED BY G.C.



- 2'x4' SUSPENDED COMPASSO CEILING GRID SYSTEM (#002 SILVER SATIN FINISH & "GRIDWARE" GWDX GRID SYSTEM) W/ 6" TALL PROFILE OVER ISLANDS. INSTALL 2'x4' WASHABLE CEILING TILES (AC-703). G.C. TO SUPPLY/INSTALL ALL REQUIRED HARDWARE & SYSTEM COMPONENTS. SEE DECOR DRAWINGS BY DFAB FOR ADDITIONAL HANGING DECOR AND SIGNAGE.

529
A13

SCALE: 1 1/2" = 1'-0"

1. THE EXISTING ROOF IS TO REMAIN. PORTIONS OF THE ROOF TO BE PATCHED & REPAIRED OR REWORKED AS REQUIRED DUE TO ANY DEMOLITION, REMOVAL OF EXISTING ITEMS, ANY NEW CONSTRUCTION, AND INSTALLATION OF NEW ITEMS. MATCH EXISTING ROOFING MATERIAL (E. MEMBRANE, INSULATION, STEEL DECKING) AND PROVIDE NEW MATERIAL AS REQUIRED TO PATCH / REPAIR ROOF AND MATCH EXISTING SLOPE.

-

527
A5.2

NO SCALE



NO SCALE



NO SCALE