

DEFLECTION TRACK TO BE USED AT BOTTOM OF JOISTS. CONSISTS OF 3' LONG LEG TO PROVIDE 1" TO 1 1/2" OF VERTICAL MOVEMENT. DOES NOT ATTACH TO JOIST WALLS OR COVERED ROOF. SEE REFLECTION TRACK. HOLD GYPSUM BOARD SHOT OF DECK BY 1/2".

GYPSUM BOARD: TYPICAL 1/2" GYP. BOARD USED UNLESS NOTED OTHERWISE. REMODEL PROJECTS USE 5/8" GYPSUM BOARD WHERE EXISTING 5/8" GYPSUM BOARD IS IN PLACE.

MOSTLY RESISTANT GYPSUM BOARD: 1/2" THICK UNLESS NOTED OTHERWISE.

CEMENT BOARD: 1/2" UNLESS NOTED OTHERWISE.

METAL STUDS: STANDARD DEPTH TO BE 3/8" UNLESS NOTED OTHERWISE. REFER TO DETAILS FOR ALL METAL STUDS.

BRACING AT COOLER PERIMETER: FULL HEIGHT WALLS BUILT ALONG COOLER/REEFER PANELS SHOULD BE BRACED AT ROOF PANEL TO ZED BRACING PER METAL STUD.

GYPSUM BOARD AT PHARMACY GRILLE: INSTALL GYPSUM BOARD AS FAR AS POSSIBLE TO COVER ALL PHARMACY GRILLES. CONSIDER WHICH SIDE WILL BE VIEWED MOST BY CUSTOMERS WHEN INSTALLING GYPSUM BOARD. FLOOR FINISH AND FINISH: REFER TO INTERIOR DECOR SPECIFICATIONS & ROOM FINISHES. FOR WALL FINISHES REFER TO CLIFICATION SECTIONS 1 AND 9.

FINISHED CEILING: EXTEND GYP. @ ABOVE CEILING. METAL STUDS DO NOT NEED TO KENZO TO DECK (U.N.O) IF BRACING BACK TO STRUCTURE ABOVE AT 4' O.C. MAX.

WOOD ROOF PANELS: ALLOWED FOR SG CONSTRUCTION. USE FRIT WOOD PANELS OR MONOCOMBINATION CONSTRUCTION.

ALL PARTITION WITH RECESSED ELECTRIC PANELS AND TILES MUST BE 6" STUD.

ALL PARTIAL HEIGHT WALLS IN SUSHI AND CHEESE SHOP LOCATIONS TO BE 4' FT. OUTLET. OUTLET OVER TOP OF EQUIPMENT ARE TO BE INSTALLED ALONG WALLS ARE TO BE INSTALLED ABOVE TABLE SPLASH

