



## Lexmark T650dtn

Part #:30G0107



### Goes the Distance

Enhanced input capacity on this network-ready powerhouse make it perfect for any performance-seeking business.

**\$1,099<sup>00</sup>**

In Stock

Quantity

1

**ADD TO CART**

[OTHER WAYS TO BUY](#)

**FREE SHIPPING ON ORDERS OVER \$25**



Extra Paper  
Tray



Security



Network



Duplex (2-  
sided)



Direct USB

[Watch Demo](#)

[View Photos](#)

[Ask Questions](#)

[Download Brochure](#)

[Features](#)

[Specs](#)

[Ink and Toner](#)

[Paper](#)

[Accessories](#)

Print Technology	Monochrome Laser
Print Resolution, Black	1200 Image Quality 1200 x 1200 dpi 2400 Image Quality 600 x 600 dpi
Print Speed (Letter, Black): Up to	45 ppm
Print Speed (A4, Black): Up to	43 ppm
Print Speed (Letter, Black) Duplex: Up to	36 spm
Print Speed (A4, Black) Duplex: Up to	35 spm
Time to First Page (Black) As fast as	7.5 seconds
Processor	500 MHz
Memory, Standard	128 MB
Memory, Maximum	640 MB
Printable Area	0.167 inches of the top, bottom, right and left edges (within)
Printable Area (metric)	4.2 mm of the top, bottom, right and left edges (within)

### Similar Products to Consider

	Paper Labels Plain Paper Polyester Labels Transparencies Vinyl Labels Refer to the Card Stock & Label Guide
<b>Number of Paper Inputs, Standard</b>	3
<b>Number of Paper Inputs, Maximum</b>	6
<b>Duplex (2-sided) Printing</b>	Includes Duplex Unit
<b>Apple Macintosh Operating Systems Supported</b>	Apple Mac OS X Apple Mac OS 9.2
<b>Microsoft Windows Operating Systems Supported</b>	Microsoft Windows 2000 Microsoft Windows XP Microsoft Windows Server 2003 Microsoft Windows XP x64 Microsoft Windows Server 2003 running Terminal Services Microsoft Windows 2000 Server running Terminal Services Microsoft Windows Server 2003 x64 Microsoft Windows Server 2003 x64 running Terminal Services Microsoft Windows Vista Microsoft Windows Vista x64 Microsoft Windows Server 2008 Microsoft Windows Server 2008 x64 Microsoft Windows Server 2008 running Terminal Services Microsoft Windows Server 2008 x64 running Terminal Services Microsoft Windows 7
<b>Novell Operating Systems Supported</b>	Novell® Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS) Novell NetWare® 3.2, 4.2 (bindery) Novell NetWare 4.2, 5.x and 6.x (NDS) Novell NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)
<b>Linux Operating Systems Supported</b>	Linpus Linux Desktop 9.2, 9.3 Red Hat Enterprise Linux WS 3.0, 4.0, 5.0 SUSE Linux Enterprise Server 8.0, 9.0, 10, 11 SUSE Linux Enterprise Desktop 10 openSUSE 10.2, 10.3, 11.0, 11.1 Linspire Linux 6.0 Debian GNU/Linux 4.0 Red Flag Linux Desktop 5.0, 6.0 Ubuntu 7.10 Ubuntu 8.04 LTS SUSE Linux Enterprise Desktop 11 Debian GNU/Linux 5.0 Ubuntu 8.10, 9.04
<b>UNIX Operating Systems Supported</b>	Sun Solaris SPARC 8, 9, 10 Sun Solaris x86 10 HP-UX 11.11, 11.23, 11.31 IBM AIX 5.2, 5.3, 6.1
<b>Other Operating Systems Supported</b>	IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform Virtually any platform supporting TCP/IP
<b>Citrix MetaFrame</b>	Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 3.0, 4.0 Microsoft Windows Server 2003 running Terminal Services with Citrix Presentation Server 3.0, 4.0, 4.5 Microsoft Windows Server 2003 x64 running Terminal Services with Citrix Presentation Server 4.0 x64, 4.5 x64
<b>Standard Ports</b>	One Internal Card Slot USB 2.0 Specification Hi-Speed Certified (Type B) Front USB Port Compatible with USB 2.0 Specification (Type A) Ethernet 10/100BaseTX (RJ-45), also works with 1000Base-T
<b>Optional Local Ports</b>	Internal RS-232C serial Internal 1284-B Bidirectional Parallel
<b>Optional Network Ports</b>	Lexmark N4050e 802.11g Wireless Print Server (Print Only) External MarkNet™ N7020e Gigabit Ethernet Internal MarkNet™ N8120 Gigabit Ethernet Internal MarkNet™ N8130 Fiber Fast Ethernet Internal MarkNet™ N8150 802.11b/g/n Wireless

<b>Printer Languages (Standard)</b>	PCL 5e Emulation PCL 6 Emulation Personal Printer Data Stream (PPDS) PostScript 3 Emulation xHTML PDF 1.6 Direct Image Microsoft XPS (XML Paper Specification)
<b>Fonts and Symbol Sets</b>	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 158 scalable PostScript fonts 2 PCL bitmap fonts 39 scalable PPDS fonts 5 PPDS bitmap fonts 84 scalable PCL fonts OCR-A, OCR-B scalable PCL 5e fonts For more information, refer to the Technical Reference.
<b>Network Protocol Support</b>	TCP/IP IPv4 IPX/SPX AppleTalk™ LexLink (DLC) TCP/IP IPv6 TCP UDP
<b>Network Printing Methods</b>	LPR/LPD Direct IP (Port 9100) Socket (Raw TCP/IP) HTTP NDS Queue-based Printing NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services) Enhanced IP (Port 9400) FTP, TFTP IPP 1.1 (Internet Printing Protocol) ThinPrint .print integration
<b>Network Security</b>	SNMPv3 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS IPSec
<b>Network Management Protocols</b>	HTTP HTTPs (SSL*/TLS) SNMPv3 WINS IGMP BOOTP, RARP APIPA (AutoIP) DHCP ICMP DNS SNMPv2c Bonjour DDNS mDNS ARP NTP Telnet Finger *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.
<b>Size (in. - H x W x D)</b>	21 x 16.7 x 25.2 in.
<b>Packaged Size (in. - H x W x D)</b>	30.31 x 37.01 x 21.06 in.
<b>Weight (lb.)</b>	60.7 lb.
<b>Size (mm - H x W x D)</b>	533 x 425 x 640 mm
<b>Packaged Size (mm - H x W x D)</b>	770 x 940 x 535 mm
<b>Weight (kg)</b>	27.4 kg
<b>Product Warranty</b>	1-Year Exchange Service, Next Business Day
<b>Packaged Weight (lb.)</b>	85.01 lb.
<b>Packaged Weight (kg)</b>	38.56 kg
<b>UNSPSC Code</b>	43212105
<b>Product Certifications</b>	Energy Star, Blue Angel (RAL-UZ-122), CAN/CSA-C22.2 60950-1, CSA E60825-1, ICES-003 Class B, BSMI Class B, CNS 13438, VCCI Class B, US FDA, FCC Class B, UL 60950-1, IEC 320-1, EN/IEC 60320-1, CE Class B, CB IEC 60950-1, EN 60950-1, EN/IEC 61000-3, EN 55022 Class B, EN 55024, EN/IEC 60825-1, GS (TÜV), SEMKO, UL AR, CS, TÜV Rh,

	SMA C-tick mark Class B, CCC Class B, CISPIR 22 Class B, EK Mark, N Mark
Country of Origin	China (PR)
Display	4-line 160 x 64 pixel All Points Addressable (APA) backlit gray-scale display
Energy Star Typical Electricity Consumption (TEC)	6.01 kilowatt-hours per week
Energy Star	Yes
Ethernet Network	Yes
Direct USB	Yes
Extra Paper Tray	Yes

[VIEW SHORT LIST](#)