



KROGER SUPPLIED & CONTRACTOR INSTALLED EQUIPMENT:


TA-1	SOAP DISPENSER.
TA-3	PAPER TOWEL MANUAL "TENSION" DISPENSER.
TA-11	COAT HOOKS PER LOCATIONS INDICATED ON PLANS. INSTALL HOOK 4'-0" ABOVE FLOOR, UNLESS NOTE OTHERWISE.



1. EXISTING COLUMN WRAPS TO REMAIN. REPLACE ANY DAMAGED COLUMN WRAPS AND RESEAL EDGES. COLUMN WRAP TO BE TO 5'-0" AFF (OR TO MATCH HEIGHT OF EXISTING COLUMN WRAPS) PER DETAIL ASD-63, SHEET A5.11. SEE PROJECT SPECIFICATIONS SECTION 01 61.13. SEE GISD-50, SHEET A512, FOR COLUMNS THAT FALL WITHIN SHELVING. COLUMNS WITH-IN PREP AREAS TO BE STAINLESS STEEL FROM FLOOR TO CEILING, SEE ASD-63, A5.11.
2. PARTITIONS TO BOTTOM OF DECK OR JOIST AND PARTITIONS WITH RECESSED EQUIPMENT (ELECTRIC PANELS, FLY GRIDS, ETC) OR PLUMBING FIXTURES SHALL BE 6" METAL STUDS.
3. PROVIDE WOOD BLOCKING (INSERTED IN METAL STUDS) IN PARTITION THIS AREA, FOR SHELVING BRACKET SUPPORT (6'-0" TO 9'-0"). FOR BABY CHANGING STATION (FROM FLOOR TO 8'-0"), EXHAUST HOOD/STAINLESS STEEL (FROM FLOOR TO 9'-0"), FOR WALL MOUNTED FIRE EXTINGUISHERS AND/OR ELECTRICAL PLUMBING FIXTURES AND SHELVING AS REQUIRED. SEE SPECIFICATIONS SECTION 06 10 53 FOR ADDITIONAL BLOCKING INFORMATION. PATCH/REPAIR WALL & FINISHES AS REQUIRED WHEN ADDING BLOCKING TO EXISTING WALLS.
4. REMOVABLE PROTECTIVE POST(S) (SALES AREA), SEE SPECS. POST(S) TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET. SEE ASD-19 ON SHEET A5.11.
5. REFRIGERATED CASE CORNER GUARD (SALES AREA), SEE SPECS. GUARD(S) TO BE SUPPLIED & INSTALLED BY GENERAL CONTRACTOR AFTER EQUIPMENT IS SET. SEE ASD-160 ON SHEET A5.12.
6. PROVIDE S.S. CORNER GUARD. SEE ASD-55A, SHEET A5.11. REPLACE ANY MISSING OR DAMAGED CORNER GUARDS.
7. PROVIDE NEW SUBSTRATE AND PREP TO RECEIVE NEW FINISHES AS REQUIRED FOR NEW WALL OR DUE TO REMOVAL OF EXISTING FINISHES. SUBSTRATE TO BE CEMENT BOARD TO 48" AFF & MOISTURE RESISTANT GYPSUM BOARD TO CEILING AT PREP AREAS AND RESTROOMS (AT NEW WALL TILE & FRP). PROVIDE GYPSUM BOARD AT ALL OTHER AREAS AS REQUIRED. PROVIDE A CLEAN FLUSH SURFACE TO APPLY NEW WALL FINISH AS INDICATED.
8. INCLUDE ALL REQUIRED TRADES, LABOR AND MATERIALS TO TEMPORARILY MOVE ALL EQUIPMENT, FIXTURES, & ACCESSORIES FOR INSTALLATION OF NEW FLOOR AND/OR WALL FINISHES AS INDICATED ON SHEETS A16 & 114.
9. MODIFY WALL, PATCH & REPAIR AS REQUIRED FOR REFRIGERATION LINE WORK. COORDINATE LOCATIONS WITH REFRIGERATION TRADE. SEE DETAIL 521, SHEET A5.2.
10. ALL NEW REFRIGERATION, PLUMBING, AND ELECTRICAL CONDUIT DROPS ON THE SALES FLOOR ARE TO BE RIGHT-ANGLED, SECURED SIMILAR TO RISD-34B AND RISD-35 ON SHEET R5.1, AND PAINTED TO MATCH COLUMNS.
11. ALL NEW REFRIGERATION AND ELECTRICAL CONDUIT CHASES AT ISLAND CASES AND FRONT LINE SERVICE CASES ARE TO BE ENCLOSED IN PVC TUBING AND PAINTED TO MATCH COLUMNS. SEE REFRIGERATION LAYOUT ON SHEET R11 AND DETAILS RISD-36 AND RISD-36A ON SHEET R5.1. FOR CHASES THAT EXTEND TO THE FLOOR, COVER WITH STAINLESS STEEL COLUMN WRAP FROM FLOOR TO 5'-0" AFF (TO MATCH HEIGHT OF EXISTING COLUMN WRAPS). SIMILAR TO ASD-63 ON SHEET A5.11.
12. NEW KITCHENETTE MILLWORK (CABINETS, COUNTER, SINK, TA-1 & TA-3). PLAN NOTE 3. SEE PLUMBING SHEETS.
13. MOUNTING HEIGHT FOR MISCELLANEOUS TOILET ROOM FIXTURES SHALL NOT EXCEED 3'-4" ABOVE FLOOR.
14. NEW DIGITAL MONITOR MENU BOARDS (2). HANG/MOUNT ABOVE SOFFIT. SEE SIMILAR DETAIL ASD-72A ON A5.12 FOR MOUNTING DETAILS. GC TO PROVIDE POWER. KROGER VENDOR TO INSTALL, TEST AND PROVIDE. INSTALL ALL REQUIRED HARDWARE (UNISUT, THREADED ROD, AND MOUNTING BRACKET). KROGER TO PROVIDE ALL LOW VOLTAGE WORK. ADJUST ANGLE & HEIGHT OF MONITORS FOR BEST VIEW OF THE DISPLAY. VERIFY LOCATION WITH KROGER PM.



PHARMACY
ENLARGED FLOOR PLAN
SCALE: 1/2" = 1'-0"



411
A11

**FLORAL STORAGE
ENLARGED FLOOR PLAN**

SCALE: 1/2" = 1'-0"

- SEE GENERAL NOTES ON SHEET A1.1
- SEE SHEET I1.4 FOR FINISHES DECOR, MILLWORK, & FIXTURE / CASE NOTES.

EXISTING WALL	EXISTING SOFFIT
NEW WALL	NEW SOFFIT


issued for:	BIDS AND PERMITS	06/12/2025
	90% OWNER REIEW	05/16/2025

**PROPOSED MINOR INTERIOR
REMODEL FOR:**



STORE NO. D-663
26130 GRATIOT AVE,
ROSEVILLE, MI 48066

THE KROGER CO. OF MICHIGAN



jeffery a.
scott
architects p.c.

32316 grand river ave. suite 200
farmington, michigan 48336-3261
(248) 476-8800 fax (248) 476-8833

ENLARGED PLANS, DETAILS, NOTES

project no.	sheet no.
-------------	-----------

24007

A4.1